



DeepCool PL650D power supply unit 650 W 20+4 pin ATX ATX White

Modelis: R-PL650D-FC0W-JDEU-V2

Gamintojas: DEEPCOOL

EAN: 6933412721246

Prekės kodas: 577854

67.99€

Certification: CE/FCC/CCC/RCM/EAC/CAN ICES-003(B)/NMB-003(B) /TUV-RH | Sustainability certificates: ErP | PCI Express power connectors (16-pin): 1 | Sustainability certificates: Triman | Sustainability compliance: Yes | Peripheral (Molex) power connectors (4-pin): 2 | Cooling type: Active | PCI Express power connectors (6+2 pin): 3 | AC input voltage: 100 - 240 V | Combined power (+3.3V): 100 W | Motherboard power cable length: 55 cm | Depth: 140 mm | Purpose: PC | Power Factor Correction (PFC) type: Active | Efficiency: 85% | Input current: 9 - 4.5 A | AC input frequency: 50/60 Hz | Width: 150 mm | Operating temperature (T-T): 0 - 40 °C | Fan location: Top | Cabling type: Non-Modular | Combined power (-12V): 3.6 W | Power protection features: No load operation | Package type: Box | Power protection features: Under voltage | Power protection features: Over current | Power protection features: Over voltage | Power protection features: Over power | Power protection features: Surge & inrush protection (SIP) | 80 PLUS certification: 80 PLUS Bronze | Mean time between failures (MTBF): 100000 h | Hold time: 16 ms | On/off switch: Yes | Height: 86 mm |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Max output current (+12V): 54 A | Combined power (+12V): 648 W | Bearing technology: HYB | Power supply unit (PSU) form factor: ATX | Combined power (+5V): 100 W | Combined power (+5Vsb): 15 W | Total power: 650 W | Max output current (+3.3V): 20 A | Power protection features: Overheating | Power protection features: Surge protection | Product colour: White | ATX version: 3.0 | Number of fans: 1 fan(s) | Fan diameter: 12 cm | Max output current (+5V): 20 A | CPU power connector (4+4 pin): Yes | SATA power cable length: 650 mm | SATA power cable length: 550 | ATX power connector (20+4 pin): Yes | Max output current (-12V): 0.3 A | Max output current (+5Vsb): 3 A | Number of SATA power connectors: 6 | SATA power cable length: 450 | Motherboard power connector: 20+4 pin ATX | Power Good signal delay range: 100 - 150 ms | Compliance certificates: RoHS | Compliance certificates: WEEE