



TP-Link 300 Mbps Wireless N 4G LTE Router



Modelis: TL-MR105

Gamintojas: TP-LINK

EAN: 4895252503371

Prekės kodas: 577857

52.99€

Depth: 130 mm | Ethernet LAN: Yes | Ethernet LAN (RJ-45) ports: 2 | Firewall: Yes | Universal Plug and Play (UPnP): Yes | Ethernet WAN: Yes | Operating temperature (T-T): 0 - 40 °C | Quick installation guide: Yes | Product colour: White | 4G bands supported: 1800 | SIM card slot: Yes | 4G bands supported: 900 | 4G bands supported: 2600 MHz | 4G bands supported: 850 | 4G bands supported: 2500 | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11b | 4G standard: LTE-TDD & LTE-FDD | Wi-Fi band: Single-band (2.4 GHz) | 3G standards: UMTS | DHCP client: Yes | 4G bands supported: 2300 | 4G bands supported: 2100 | 4G bands supported: 800 | Package type: Box | DMZ support: Yes | Port triggering: Yes | Width: 174 mm | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | WLAN data transfer rate (max): 300 Mbit/s | Security algorithms: WPA | Sustainability certificates: CE | Security algorithms: WPA2-PSK | WPS push button: Yes | Sustainability compliance: Yes | Reset button: Yes | 3G standards: HSPA | WLAN data transfer rate (first band): 300 Mbit/s | Port forwarding: Yes | DHCP server: Yes | 3G standards: DC-HSPA+ | 3G standards: HSDPA | Firewall security: IPv4 SPI Firewall | Dynamic DNS (DDNS): Yes | Power source type: DC | Sustainability certificates: RoHS | Ethernet LAN interface type: Fast Ethernet

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

| DC-in jack: Yes | Ethernet LAN data rates: 10 | USB port: No | SIM card type: NanoSIM | WAN connection type: RJ-45 | Operating relative humidity (H-H): 10 - 90% | Product type: Tabletop router | Cables included: LAN (RJ-45) | Height: 60 mm | Mobile network generation: 4G | Antenna design: Internal | Guest access: Yes | Number of guest networks (2.4 GHz): 1 | Security algorithms: 128-bit WEP | Ethernet LAN data rates: 100 Mbit/s