



Gamer Storm PS850G WH power supply unit 850 W 20+4 pin ATX ATX White

Modelis: R-PS850G-FE0W-JGEU

Gamintojas: DEEPCOOL

EAN: 6933412755272

Prekės kodas: 577947

117.99€

Certification: Cybenetics Platinum/PPLP Gold | Operating temperature (T-T): 0 - 40 °C | AC input voltage: 100 - 240 V | Input current: 10 - 5 A | Peripheral (Molex) power connectors (4-pin): 1 | Product colour: White | Package type: Box | Cables included: CPU, PCIe, Peripheral (Molex), SATA, AC | Cooling type: Active | AC input frequency: 50/60 Hz | Manual: Yes | Max output current (+5Vsb): 3 A | PCI Express power connectors (16-pin): 1 | Number of SATA power connectors: 3 | Bearing technology: FDB | CPU power cable length: 50 cm | Combined power (-12V): 3.6 W | Motherboard power connector: 20+4 pin ATX | Fan diameter: 9.2 cm | ATX version: 3.1 | Combined power (+5Vsb): 15 W | Total power: 850 W | Warranty period: 5 year(s) | Cabling type: Fully-Modular | Efficiency: 90% | Sustainability certificates: ErP | Sustainability certificates: Triman | Power protection features: Under voltage | Power protection features: Over current | Peripheral (Molex) power cable length: 120 | PCI Express power connectors (6+2 pin): 3 | Max output current (+5V): 20 A |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Compliance certificates: RoHS | Compliance certificates: CE | Motherboard power cable length: 35 cm | Compliance certificates: EAC | Max output current (+3.3V): 20 A | Compliance certificates: CCC | Power protection features: Overheating | Power protection features: Surge & inrush protection (SIP) | Power protection features: Short circuit | Power protection features: Over voltage | Compliance certificates: TÜV mark | Power protection features: Over power | Cable tie(s) included: Yes | Compliance certificates: ICES | Max output current (-12V): 0.3 A | SATA power cable length: 300 mm | Depth: 100 mm | Mean time between failures (MTBF): 100000 h | Compliance certificates: RCM | Power protection features: No load operation | Height: 63.5 mm | Combined power (+3.3V): 100 W | Max output current (+12V): 70.8 A | PCI Express power cable length: 45 cm | Combined power (+5V): 100 W | PCI Express connector: Yes | CPU power connector (4+4 pin): Yes | Purpose: PC | SATA power cable length: 120 | Power Factor Correction (PFC) type: Active | Compliance certificates: KC | Number of fans: 1 fan(s) | Power supply unit (PSU) form factor: ATX | Hold time: 16 ms | Width: 125 mm | Combined power (+12V): 849.6 W