



DeepCool PS850G power supply unit 850 W 20+4 pin ATX SFX Black

Modelis: R-PS850G-FE0B-JGEU

Gamintojas: DEEPCOOL

EAN: 6933412755197

Prekės kodas: 577948

114.99€

Certification: Cybenetics Platinum/PPLP Gold ATX3.1 | AC input voltage: 100 - 240 V | Power supply unit (PSU) form factor: SFX | Package type: Box | Efficiency: 90% | Product colour: Black | Depth: 100 mm | Fan diameter: 9.2 cm | Input current: 10 - 5 A | Peripheral (Molex) power connectors (4-pin): 1 | Mean time between failures (MTBF): 100000 h | PCI Express power connectors (6+2 pin): 3 | Power protection features: Overheating | Total power: 850 W | Cooling type: Active | Cabling type: Fully-Modular | Height: 63.5 mm | Combined power (+3.3V): 100 W | Number of fans: 1 fan(s) | Power protection features: Over power | Sustainability certificates: ErP | Sustainability certificates: Triman | Power protection features: No load operation | Combined power (-12V): 3.6 W | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Under voltage | Power protection features: Over current | Power protection features: Surge & inrush protection (SIP) | Warranty period: 5 year(s) | Operating temperature (T-T): 0 - 40 °C | PCI Express power connectors (16-pin): 1 | Purpose: PC | Power Factor Correction (PFC) type: Active | Combined

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

power (+5V): 100 W | Manual: Yes | AC input frequency: 50/60 Hz | Combined power (+12V): 849.6 W | Cables included: CPU, PCIe, Peripheral (Molex), SATA, AC | Width: 125 mm | Compliance certificates: CCC | Compliance certificates: EAC | Compliance certificates: TÜV mark | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: KC | Compliance certificates: ICES | Compliance certificates: RCM | Bearing technology: FDB | Hold time: 16 ms | Cable tie(s) included: Yes | ATX version: 3.1 | CPU power connector (4+4 pin): Yes | Combined power (+5Vsb): 15 W | Number of SATA power connectors: 3 | Max output current (+5Vsb): 3 A | Peripheral (Molex) power cable length: 120 | CPU power cable length: 50 cm | Max output current (+12V): 70.8 A | SATA power cable length: 300 mm | Max output current (+5V): 20 A | SATA power cable length: 120 | Motherboard power connector: 20+4 pin ATX | Motherboard power cable length: 35 cm | PCI Express connector: Yes | Max output current (+3.3V): 20 A | Max output current (-12V): 0.3 A | PCI Express power cable length: 45 cm