



## Gamer Storm PS750G WH power supply unit 750 W 20+4 pin ATX ATX White

Modelis: R-PS750G-FE0W-JGEU

Gamintojas: DEEPCOOL

EAN: 6933412755111

Prekės kodas: 577949

# 107.99€

Certification: Cybenetics Platinum/PPLP Gold | Operating temperature (T-T): 0 - 40 °C | Product colour: White | Cooling type: Active | Peripheral (Molex) power connectors (4-pin): 1 | AC input frequency: 50/60 Hz | Package type: Box | AC input voltage: 100 - 240 V | Input current: 10 - 5 A | Efficiency: 90% | Cabling type: Fully-Modular | Max output current (+12V): 62.5 A | Max output current (+5V): 20 A | Cable tie(s) included: Yes | Power Factor Correction (PFC) type: Active | Motherboard power connector: 20+4 pin ATX | Sustainability certificates: Triman | Power protection features: Overheating | Power protection features: Over power | Depth: 100 mm | SATA power cable length: 300 mm | Combined power (-12V): 3.6 W | SATA power cable length: 120 | Purpose: PC | Number of fans: 1 fan(s) | Bearing technology: FDB | CPU power cable length: 50 cm | Manual: Yes | Sustainability certificates: ErP | Power protection features: Under voltage | Power protection features: Over current | PCI Express power connectors (6+2 pin): 3 | Power protection features: Surge & inrush

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

protection (SIP) | Warranty period: 5 year(s) | Number of SATA power connectors: 3 | Power protection features: Short circuit | Power protection features: Over voltage | Max output current (+5Vsb): 3 A | Power protection features: No load operation | Combined power (+3.3V): 100 W | Height: 63.5 mm | Motherboard power cable length: 35 cm | Max output current (+3.3V): 20 A | Combined power (+5V): 100 W | Width: 125 mm | Combined power (+12V): 750 W | Peripheral (Molex) power cable length: 120 | Mean time between failures (MTBF): 100000 h | Cables included: CPU, PCIe, Peripheral (Molex), SATA, AC | PCI Express connector: Yes | Power supply unit (PSU) form factor: ATX | Combined power (+5Vsb): 15 W | Hold time: 16 ms | Fan diameter: 9.2 cm | ATX version: 3.1 | Total power: 750 W | PCI Express power cable length: 45 cm | CPU power connector (4+4 pin): Yes | Max output current (-12V): 0.3 A | Compliance certificates: ICES | Compliance certificates: RCM | Compliance certificates: EAC | Compliance certificates: TÜV mark | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: KC | Compliance certificates: CCC | PCI Express power connectors (16-pin): 1