



Gamer Storm PS750G power supply unit 750 W 20+4 pin ATX SFX Black

Modelis: R-PS750G-FE0B-JGEU

Gamintojas: DEEPCOOL

EAN: 6933412755036

Prekės kodas: 577950

106.00€

Certification: Cybenetics Platinum/PPLP Gold ATX3.1 | PCI Express power connectors (16-pin): 1 | Compliance certificates: RCM | Compliance certificates: EAC | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: KC | Compliance certificates: CCC | Compliance certificates: ICES | Compliance certificates: TÜV mark | Warranty period: 5 year(s) | Combined power (-12V): 3.6 W | Total power: 750 W | PCI Express power connectors (6+2 pin): 3 | Power supply unit (PSU) form factor: SFX | Bearing technology: FDB | Combined power (+5V): 100 W | Sustainability certificates: ErP | Sustainability certificates: Triman | Cabling type: Fully-Modular | ATX version: 3.1 | Efficiency: 90% | Power Factor Correction (PFC) type: Active | Combined power (+3.3V): 100 W | Combined power (+12V): 750 W | Mean time between failures (MTBF): 100000 h | Hold time: 16 ms | Combined power (+5Vsb): 15 W | Number of SATA power connectors: 3 | Max output current (+5Vsb): 3 A | CPU power cable length: 50 cm | CPU power connector (4+4 pin): Yes | Max output current (+12V): 62.5 A | SATA power cable length: 300 mm | SATA power cable length: 120 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Peripheral (Molex) power cable length: 120 | Motherboard power cable length: 35 cm | Motherboard power connector: 20+4 pin ATX | Height: 63.5 mm | Max output current (+3.3V): 20 A | Power protection features: Under voltage | Power protection features: Over current | PCI Express connector: Yes | Width: 125 mm | Peripheral (Molex) power connectors (4-pin): 1 | Cooling type: Active | Power protection features: Short circuit | Power protection features: Over voltage | Max output current (-12V): 0.3 A | Cables included: CPU, PCIe, Peripheral (Molex), SATA, AC | Cable tie(s) included: Yes | Power protection features: Over power | Operating temperature (T-T): 0 - 40 °C | Power protection features: No load operation | Depth: 100 mm | PCI Express power cable length: 45 cm | Power protection features: Overheating | Manual: Yes | AC input frequency: 50/60 Hz | Max output current (+5V): 20 A | AC input voltage: 100 - 240 V | Power protection features: Surge & inrush protection (SIP) | Product colour: Black | Input current: 10 - 5 A | Number of fans: 1 fan(s) | Package type: Box | Purpose: PC | Fan diameter: 9.2 cm