



TP-LINK TL-WA1201

wireless access point 867 Mbit/s

Power over Ethernet (PoE)

White

Modelis: TL-WA1201

Gamintojas: TP-LINK

EAN: 1210002608510

Prekės kodas: 577955

54.99€

Compatible operating systems: Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser | 2.4 GHz: Yes | DHCP client: Yes | Ethernet LAN data rates: 100 Mbit/s | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 1000 | MIMO: Yes | Product colour: White | Reset button: Yes | Antenna type: External | Maximum data transfer rate: 867 Mbit/s | 5 GHz: Yes | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11b | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | PoE adapter included: Yes | WPS push button: Yes | Power over Ethernet (PoE) type supported: Active PoE | Virtual LAN features: Multicast VLAN | Compliance

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS |
Compliance certificates: CE | Transmitting power (CE): 20 - 23 dBm | Package width: 400 mm |
Operating relative humidity (H-H): 10 - 90% | On/off switch: Yes | Transmitting power (FCC): 30 dBm |
Security algorithms: WPA | Security algorithms: WPA2-PSK | Storage temperature (T-T): -40 - 70 °C |
Quality of Service (QoS) support: Yes | AC adapter included: Yes | Quick start guide: Yes | Security
algorithms: 64-bit WEP | Security algorithms: WPA2 | Height: 37 mm | Package height: 69 mm | DHCP
server: Yes | Package weight: 860 g | Cables included: LAN (RJ-45) | Package depth: 255 mm | MIMO
type: Multi User MIMO | Depth: 145.5 mm | Service Set Identifier (SSID) features: Multiple SSIDs |
Sustainability compliance: Yes | Universal Plug and Play (UPnP): Yes | Operating temperature (T-T): 0
- 40 °C | Placement: Table | Storage relative humidity (H-H): 10 - 90% | Security algorithms: WPA-PSK
| Ethernet LAN (RJ-45) ports: 1 | Security algorithms: 128-bit WEP | Auto Wireless Distribution System
(WDS): Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Antennas quantity: 4 | VLAN support: Yes |
Maximum data transfer rate (2.4 GHz): 300 Mbit/s | 6 GHz: No | Output current: 1.5 A | Maximum
data transfer rate (5 GHz): 867 Mbit/s | Output voltage: 12 V | Access Control List (ACL): Yes | Power
over Ethernet (PoE): Yes | Width: 225 mm | Quantity per pack: 1 pc(s)