



TP-Link 8-Port Gigabit Desktop Network Switch



Modelis: TL-SG1008D

Gamintojas: TP-LINK

EAN: 1210002616645

Prekės kodas: 577957

24.99€

Certification: CE, FCC, RoHS | Package weight: 300 g | Packet buffer memory: 2 MB | Auto-negotiation: Yes | Ethernet LAN data rates: 10,100,480,800,1000 Mbit/s | Storage temperature (T-T): -40 - 70 °C | Product colour: Black | AC adapter included: Yes | Power consumption (max): 3.53 W | Operating relative humidity (H-H): 10 - 90% | Package width: 110 mm | Operating temperature (T-T): 0 - 40 °C | AC input frequency: 50/60 Hz | Full duplex: Yes | MAC address table: 4000 entries | Height: 25.5 mm | AC input voltage: 100 - 240 V | Wall mountable: Yes | LED indicators: Yes | Input current: 0.6 A | Heat dissipation: 15.8 BTU/h | Packet forwarding rate (10 Mbps): 1488000 pps | Cables included: AC | Cable types supported: Cat5 | Cable types supported: Cat5e | Copper ethernet cabling technology: 10BASE-T | Package height: 85 mm | Power source: DC | Cable types supported: Cat4 | Power consumption (typical): 4.63 W | Cable types supported: Cat3 | Packet forwarding rate (1 Gbps): 14880 pps | Power over Ethernet (PoE): No | Storage relative humidity (H-H): 5 - 90% | Package type: Box | Networking standards: IEEE 802.3u | Copper ethernet cabling technology: 1000BASE-T | Power supply included: Yes | Stackable: No | Package depth: 185 mm | User guide: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3i | Basic

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Store-and-forward: Yes | Power connector: DC-in jack | Packet forwarding rate (100 Mbps): 148800 pps | Depth: 90 mm | Auto MDI/MDI-X: Yes | DC input voltage: 9 V | Housing material: Plastic | Fanless: Yes | Rack mounting: No | 10G support: No | Copper ethernet cabling technology: 100BASE-TX | Flow control support: Yes | Switching capacity: 16 Gbit/s | Harmonized System (HS) code: 85176990 | Switch type: Unmanaged | Width: 180 mm | Jumbo frames: 15000 | Maximum cable length: 100 m | Gigabit Ethernet (copper) ports quantity: 8 | Jumbo frames support: Yes | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE | Sustainability compliance: Yes