

TP-Link 8-Port Gigabit Easy Smart Switch with 4-Port PoE

Gamintojas: **TP-LINK** · Modelis: **TL-SG108PE** · EAN: **1210002616942** · Prekės kodas: **577958**



65,90 €

Kaina su PVM

Be PVM: 54,46 €

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt



Aprašymas

Certification: FCC, CE, RoHS | Package type: Box | Package height: 121 mm | Product colour: Black | VLAN support: Yes | Power source: DC | Basic switching RJ-45 Ethernet ports quantity: 8 | Package depth: 196 mm | Web-based management: Yes | User guide: Yes | LED indicators: Status | Networking standards: IEEE 802.3i | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Input voltage: 48 V | Width: 158 mm | Cable types supported: Cat4 | LED indicators: PoE | Loop protection: Yes | LED indicators: Link | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Power over Ethernet (PoE): Yes | Package width: 131 mm | Number of VLANs: 32 | LED indicators: Speed | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.3u | IGMP snooping: Yes | LED indicators: Power | Heat dissipation: 256.19 BTU/h | Input current: 1.25 A | AC input voltage: 220 V | Switch type: Managed | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Power over Ethernet (PoE) power per port: 15.4 W | Rate limiting: Yes | Harmonized System (HS) code: 85176990 | LED indicators: Activity | Storage relative humidity (H-H): 5 - 95% | Virtual LAN features: Port-based VLAN | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat3 | Cable types supported: Cat6 | Packet forwarding rate (1 Gbps): 11900000 pps | Auto MDI/MDI-X: Yes | Packet buffer memory: 1.5 MB | Port mirroring: Yes | AC input frequency: 50 Hz | Power supply included: Yes | 10G support: No | Height: 25 mm | Cables included: AC | Operating temperature (T-T): 0 - 40 °C | Package weight: 860 g | MAC address table: 4000 entries | Auto-negotiation: Yes | Operating relative humidity (H-H): 10 - 90% | Total Power over Ethernet (PoE) budget: 64 W | Switch layer: L2 | Power over Ethernet (PoE) ports quantity: 4 | Depth: 101 mm | Power consumption (max): 65.2 W | Switching capacity: 16 Gbit/s | Broadcast storm control: Yes | Store-and-forward: Yes | Jumbo frames support: Yes | Jumbo frames: 15000 | Power over Ethernet plus (PoE+) ports quantity: 4 | Forwarding rate: 11.9 Mpps | Gigabit Ethernet (copper) ports quantity: 8 | Link aggregation: Yes

Techninė specifikacija

Specifications

Sandėlio grupė	Switches [+94][-61]
----------------	---------------------

Matmenys ir svoris

Matmenys (l × p × A)	13,00cm × 12,00cm × 20,00cm
----------------------	-----------------------------

Svoris	0,89kg
--------	--------