



TP-Link 18-Port Gigabit Rackmount Switch with 16 PoE+



Modelis: TL-SG1218MP

Gamintojas: TP-LINK

EAN: 1210002617086

Prekės kodas: 577959

198.98€

Certification: CE, FCC, RoHS | AC input frequency: 50 - 60 Hz | Power supply included: Yes | Operating relative humidity (H-H): 10 - 90% | Housing material: Metal | Storage relative humidity (H-H): 5 - 90% | Product colour: Black | Package height: 80 mm | Quick start guide: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Height: 44 mm | Ethernet LAN data rates: 10,100,1000 Mbit/s | Package depth: 528 mm | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Form factor: 1U | Flow control support: Yes | Basic switching RJ-45 Ethernet ports quantity: 18 | Switching capacity: 36 Gbit/s | LED indicators: Yes | Power consumption (max): 286.64 W | Power over Ethernet plus (PoE+) ports quantity: 16 | Forwarding rate: 26.78 Mpps | 10G support: No | Package weight: 3.05 kg | Cables included: AC | Full duplex: Yes | Cable types supported: Cat3 | Power source: AC | Cable types supported: Cat4 | Package width: 250 mm | Depth:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

180 mm | Switch type: Unmanaged | Cable types supported: Cat6 | Gigabit Ethernet (copper) ports quantity: 18 | Jumbo frames: 10000 | MAC address auto-aging supported: Yes | Total Power over Ethernet (PoE) budget: 250 W | Packet buffer memory: 4.1 MB | MAC address table: 8000 entries | Auto-negotiation: Yes | Heat dissipation: 977.44 BTU/h | Number of fans: 2 fan(s) | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Operating temperature (T-T): 0 - 50 °C | Cable types supported: Cat5 | Cable types supported: Cat5e | AC input voltage: 100 - 240 V | Auto MDI/MDI-X: Yes | Combo SFP ports quantity: 2 | Half duplex: Yes | Jumbo frames support: Yes | Harmonized System (HS) code: 85176990 | MAC address auto-learning supported: Yes | Rack mounting: Yes | Power over Ethernet (PoE): Yes | Traffic classification: Yes | Width: 440 mm