



Zyxel GS1200-10v3 Managed L2 Gigabit Ethernet (10/100/1000) Desktop Grey

Modelis: GS1200-10V3-EU0101F

Gamintojas: ZYXEL

EAN: 4718937649761

Prekės kodas: 578345

44.00€

Certification: CE-LVD, BSMI CE, EAC, FCC, BSMI Class B | MAC address table: 4000 entries | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Fanless: Yes | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Packet buffer memory: 0.192 MB | Networking standards: IEEE 802.3u | Power consumption (max): 4.165 W | Full duplex: Yes | Height: 26 mm | Operating temperature (T-T): 0 - 50 °C | Storage relative humidity (H-H): 10 - 95% | Virtual LAN features: Port-based VLAN | Port mirroring: Yes | Forwarding rate: 14.88 Mpps | Web-based management: Yes | Weight: 338 g | Width: 193 mm | Power connector: DC-in jack | Depth: 85 mm | Multicast support: Yes | Switching capacity: 20 Gbit/s | IGMP snooping: Yes | Stackable: No | Basic switching RJ-45 Ethernet ports quantity: 8 | VLAN support: Yes | Number of multicast groups filtered: 128 | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

100BASE-T | Password protection: Yes | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Networking standards: IEEE 802.3ad | 10G support: No | Power source: AC | Broadcast storm control: Yes | Product colour: Grey | Form factor: Desktop | AC input frequency: 50/60 Hz | Power over Ethernet (PoE): No | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | AC input voltage: 100 - 240 V | Heat dissipation: 14.212 BTU/h | Copper ethernet cabling technology: 1000BASE-T | DHCP features: DHCP client | Operating relative humidity (H-H): 10 - 95% | Power supply included: Yes | Jumbo frames: 15 | Jumbo frames support: Yes | Switch type: Managed | Switch layer: L2 | Rack mounting: No | Mean time between failures (MTBF): 909732 h | LED indicators: Yes | SFP module slots quantity: 2