



**Reolink W437 -
4K Wi-Fi 6
Security
Camera, IK10
Vandal-Proof,
5X Optical
Zoom, 2.4/5 GHz
Wi-Fi, Color
Night Vision**

Modelis: WC843WAD4K01

Gamintojas: REOLINK

EAN: 6975253983841

Prekės kodas: 578366

132.99€

Warnings: The product contains electronic components do not dispose of with the normal household waste. | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Mounting kit: Yes | Built-in light: Yes | Built-in microphone: Yes | Power source type: DC | Audio system: 2-way | Bluetooth: No | Supported graphics resolutions: 3840 x 2160 | Reset button: Yes | Product colour: White | DC-in jack: Yes | Connectivity technology: Wired & Wireless | Security algorithms: WPA | Networking standards:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

IEEE 802.11g | Networking standards: IEEE 802.11n | Ethernet LAN (RJ-45) ports: 1 | Networking standards: IEEE 802.11b | Maximum resolution: 3840 x 2160 pixels | Networking standards: IEEE 802.11a | Operating temperature (T-T): -10 - 55 °C | Type: IP security camera | Networking standards: IEEE 802.11ac | Security algorithms: WPA2 | Weight: 754 g | Maximum aperture number: 1.6 | Video compression formats: H.265 | Supported network protocols: HTTPS, SSL, TCP/IP, UDP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P | Operating relative humidity (H-H): 10 - 90% | Ethernet interface type: Fast Ethernet | Video formats supported: H.265 | Optical zoom: 5x | Zoom capability: Yes | DC output current: 1 A | International Protection (IP) code: IP67 | Compatible memory cards: MicroSD (TransFlash) | Height: 98.3 mm | Mac operating systems supported: Yes | Windows operating systems supported: Yes | Optical sensor size: 25.4 / 2.8 mm (1 / 2.8") | Night vision distance: 30 m | Form factor: Dome | Total megapixels: 8 MP | Number of cameras: 1 | Diameter: 13.3 cm | Supported video modes: 2160p | Bit rate: 64 Kbps - 6144 Kbps | Sensor type: CMOS | Wi-Fi: Yes | Screws included: Yes | Focal length range: 2.7 - 13.5 mm | Ethernet LAN: Yes | Wi-Fi standards: 802.11g | LED type: IR | Mobile operating systems supported: iOS | Frame rate: 15 fps | Wi-Fi standards: Wi-Fi 4 (802.11n) | Number of illumination LEDs: 4 | Built-in HDD: No | Power consumption (max): 12 W | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Card reader integrated: Yes | Mobile operating systems supported: Android | Maximum memory card size: 256 GB | Wi-Fi standards: 802.11b | Wi-Fi standards: 802.11a | DC output voltage: 12 | Placement supported: Indoor & outdoor | Built-in speaker(s): Yes | Night vision: Yes | Virtual assistant: Google Assistant | Video streaming: Yes | Live view: Yes | Infra-red wavelength: 850 nm | Infrared (IR) cut-off filter: Yes | Mounting type: Ceiling | Video motion detection: Yes | Number of users: 20 user(s) | Number of sensors: 1 | Colour temperature: 6000 K | Number of lenses: 1 | User access level: Administrator, User | Video recording: Yes | Lens viewing angle, horizontal: 31 - 105° | Lens viewing angle, vertical: 17 - 55°