

# CyberPower PR1500ERT2U uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 1500 W 10 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **PR1500ERT2U** · EAN: **4712856277609** · Prekės kodas: **578598**



## 821,90 €

Kaina su PVM

Be PVM: **679,26 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Line-Interactive
- ✓ 1.5 kVA 1500 W
- ✓ Waveform: Pure sine
- ✓ 10 AC outlet(s)
- ✓ Sealed Lead Acid (VRLA)
- ✓ Rackmount/Tower Black



## Aprašymas

### PR1500ERT2U

CyberPower PR1500ERT2U Line-Interactive UPS, with seamless Pure Sine Wave, provides the best power protection available for office system devices including PCs, workstations, networking devices, and peripherals. It's typically integrated in the back office, server room, and data center environment. The rackmount / tower convertible design gives it enhanced flexibility for installation and operation in almost any environment. Multiple UPS systems can be connected to a single main Emergency Power Off (EPO) switch. In the event of an emergency, the UPS systems can be shut down immediately with the EPO button. As for battery maintenance, the UPS allows battery hot-swapping, which enables users to perform normal battery maintenance without significant interruption.

### Critical/Noncritical Load Outlets

By dividing the outlets according to the importance of the connected loads, users are offered the flexibility to wisely manage the limited battery power during the event of power outage. In the state of a power failure, the UPS battery power can be preserve by terminating the power provided to the non-critical outlets, sparing the power to allow more runtime for critical loads to perform graceful shutdown.

#### Heavy-duty Rackmount Rails Included

The adjustable rackmount rails are engineered to facilitate the rack mounting of UPS or battery modules and support heavy UPS systems. Installation is quick and easy and required mounting hardware is included.

#### Sturdy Rackmount Ears Included

The rackmount ears are included for flexible rack mounting of UPS or battery modules. For some rack/tower convertible models, the ears also serve as supporting stands to provide stability and keep the unit upright. Installation is quick and easy and required mounting hardware is included.

### Techninė specifikacija

| Specifications                     |                                 |
|------------------------------------|---------------------------------|
| Sandėlio grupė                     | UPS power supplies [+106][-145] |
| Features                           |                                 |
| UPS topology                       | Line-Interactive                |
| Output power capacity              | 1.5 kVA                         |
| Output power                       | 1500 W                          |
| Waveform                           | Pure sine                       |
| Input operation voltage (min)      | 159 V                           |
| Input operation voltage (max)      | 288 V                           |
| Input frequency                    | 50/60 Hz                        |
| Output operation voltage (min)     | 220 V                           |
| Output operation voltage (max)     | 240 V                           |
| Output frequency                   | 50/60 Hz                        |
| Automatic Voltage Regulation (AVR) | Yes                             |
| Maximum current                    | 10 A                            |
| Surge energy rating                | 2430 J                          |
| Response time                      | 4 ms                            |
| Heat dissipation                   | 75.1 BTU/h                      |
| Number of input phases             | 1                               |
| Number of output phases            | 1                               |
| Output power factor                | 1                               |
| Power Factor Correction (PFC) type | Active                          |
| Emergency Power Off (EPO)          | Yes                             |
| EMI/RFI noise filtering            | Yes                             |

|                           |                                                                 |
|---------------------------|-----------------------------------------------------------------|
| Noise level               | 52.5 dB                                                         |
| Surge protection          | Yes                                                             |
| Surge protection features | Network                                                         |
| Power protection features | Overload                                                        |
| Audible alarm(s)          | Yes                                                             |
| Management protocols      | SNMP/HTTP                                                       |
| Audible alarm modes       | Alarm when on battery, Fault, Low battery alarm, Overload alarm |

### Ports & interfaces

|                                     |                 |
|-------------------------------------|-----------------|
| AC outlet types                     | C13 coupler     |
| Power plug                          | C14 coupler     |
| AC outlets quantity                 | 10 AC outlet(s) |
| USB port                            | Yes             |
| USB 2.0 ports quantity              | 1               |
| Serial interface                    | Yes             |
| Serial interface type               | RS-232          |
| Serial ports quantity               | 1               |
| RS-232 ports                        | 1               |
| Ethernet LAN (RJ-45) ports          | 2               |
| Emergency Power Off (EPO) connector | Yes             |

### Battery

|                                  |                         |
|----------------------------------|-------------------------|
| Battery technology               | Sealed Lead Acid (VRLA) |
| Number of batteries supported    | 1                       |
| Typical backup time at full load | 6 min                   |
| Typical backup time at half load | 18.6 min                |
| Battery recharge time            | 3 h                     |
| Hot-swap battery                 | Yes                     |

### Design

|                  |                 |
|------------------|-----------------|
| Form factor      | Rackmount/Tower |
| Product colour   | Black           |
| Housing material | Metal           |
| Rack capacity    | 2U              |
| Cable length     | 3.05 m          |
| Cooling type     | Active          |
| Built-in fan     | Yes             |
| Control type     | Buttons         |

|                                   |                      |
|-----------------------------------|----------------------|
| Display type                      | LCD                  |
| LED indicators                    | Fault, Power, Status |
| Operational conditions            |                      |
| Operating temperature (T-T)       | 0 - 40 °C            |
| Storage temperature (T-T)         | -15 - 45 °C          |
| Operating relative humidity (H-H) | 0 - 95%              |
| Storage relative humidity (H-H)   | 0 - 95%              |
| Operating altitude                | 0 - 3000 m           |
| Non-operating altitude            | 0 - 15000 m          |
| Certificates                      |                      |
| Compliance certificates           | RoHS                 |
| Packaging content                 |                      |
| Rack mount kit                    | Yes                  |
| Cables included                   | Serial, USB cable    |
| Manual                            | Yes                  |
| Weight & dimensions               |                      |
| Width                             | 433 mm               |
| Depth                             | 412 mm               |
| Height                            | 86.5 mm              |
| Weight                            | 29.4 kg              |
| Packaging data                    |                      |
| Package width                     | 560 mm               |
| Package depth                     | 530 mm               |
| Package height                    | 275 mm               |
| Package weight                    | 31.2 kg              |
| Logistics data                    |                      |
| Harmonized System (HS) code       | 8504408590           |
| Warranty period                   | 3 year(s)            |
| Country of origin                 | China                |
| Other features                    |                      |
| Battery type                      | RBP0129              |
| Sustainability                    |                      |
| Sustainability compliance         | Yes                  |
| Matmenys ir svoris                |                      |

|                      |                             |
|----------------------|-----------------------------|
| Matmenys (I × P × A) | 53,00cm × 26,00cm × 56,00cm |
| Svoris               | 31,48kg                     |