



CyberPower PR1500ERT2U uninterruptible power supply (UPS) Line- Interactive 1500 VA 1500 W 10 AC outlet(s)

Modelis: PR1500ERT2U

Gamintojas: CYBERPOWER

EAN: 4712856277609

Prekės kodas: 578598

868.99€

Battery type: RBP0129 | Certification: CE, FCC Class B, UL, RCM, VCCI | Display: LCD | Form factor: Rackmount/Tower | Power plug: C14 coupler | Storage relative humidity (H-H): 0 - 95% | Ethernet LAN (RJ-45) ports: 2 | Operating temperature (T-T): 0 - 40 °C | Cable length: 3.05 m | Product colour: Black | Output power: 1500 W | Width: 433 mm | Package width: 560 mm | Rack capacity: 2U | Operating altitude: 0 - 3000 m | USB port: Yes | USB 2.0 ports quantity: 1 | Serial ports quantity: 1 | Audible alarm(s): Yes | Number of batteries supported: 1 | Housing material: Metal | Noise level: 52.5 dB | Depth: 412 mm | RoHS compliance: Y | Storage temperature (T-T): -15 - 45 °C | Height: 86.5 mm

| Power protection features: Overload | Operating relative humidity (H-H): 0 - 95% | AC outlets

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be

išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

quantity: 10 AC outlet(s) | Package height: 275 mm | LED indicators: Yes | Battery technology: Sealed Lead Acid (VRLA) | Weight: 29.4 kg | Automatic Voltage Regulation (AVR): Yes | Output frequency: 50/60 Hz | Serial interface: Yes | Emergency Power Off (EPO) connector: Yes | UPS topology: Line-Interactive | Audible alarm modes: Low battery alarm | Battery recharge time: 3 h | Hot-swap battery: Yes | Output power capacity: 1500 kVA | Input operation voltage (min): 151 V | Waveform: Pure sine | AC outlet types: C13 coupler | Surge protection: Yes | Output operation voltage (min): 220 V | EMI/RFI noise filtering: Yes | Output power factor: 1 | Serial interface type: RS-232 | Input operation voltage (max): 302 V | Audible alarm modes: Alarm when on battery | Maximum current: 10 A | Audible alarm modes: Fault | Surge energy rating: 2430 J | Input frequency: 50/60 Hz | Audible alarm modes: Overload alarm | Emergency Power Off (EPO): Yes | Power Factor Correction (PFC) type: Active | Rack mount kit: Yes | Non-operating altitude: 0 - 15000 m | Output operation voltage (max): 240 V