



CyberPower OLS1500EA uninterruptible power supply (UPS) Double- conversion (Online) 1.5 kVA 1350 W 4 AC outlet(s)

Modelis: OLS1500EA-DE

Gamintojas: CYBERPOWER

EAN: 4711027790299

Prekės kodas: 578600

500.99€

Certification: RoHS | Output frequency: 50/60 Hz | Emergency Power Off (EPO) connector: Yes | Charging current: 1.5 A | Waveform: Pure sine | Efficiency (ECO mode): 95% | Surge energy rating: 345 J | Number of output IEC jumpers: 2 | Compliance certificates: CE | Output power: 1350 W | Audible alarm modes: Battery replacement, Fault, Low battery alarm, Overload alarm | Product colour: Black | Storage relative humidity (H-H): 10 - 90% | Audible alarm(s): Yes | Output voltage Total Harmonic Distortion (THD): 5% | Housing material: Metal | Package width: 241 mm | Input

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

power factor: 0.98 | Height: 225 mm | Maximum current: 9 A | Input frequency: 50/60 Hz | Typical backup time at half load: 15.3 min | Output operation voltage (min): 208 V | Storage temperature (T-T): -20 - 50 °C | Cables included: USB cable | Display type: LCD | Harmonized System (HS) code: 8504408590 | Operating relative humidity (H-H): 20 - 90% | Typical backup time at full load: 5.3 min | Power protection features: Overload | Operating temperature (T-T): 0 - 40 °C | EMI/RFI noise filtering: Yes | Form factor: Tower | Response time: 0 ms | Manual: Yes | Output power capacity: 1.5 kVA | AC outlet types: IEC 320 | Depth: 394 mm | Power factor: 0.9 | AC outlets quantity: 4 AC outlet(s) | Package height: 313 mm | UPS topology: Double-conversion (Online) | USB 2.0 ports quantity: 1 | Power plug: C13 coupler | Cable length: 1.5 m | Width: 151 mm | Input operation voltage (min): 190 V | Battery technology: Sealed Lead Acid (VRLA) | Operating altitude: 0 - 1500 m | Input operation voltage (max): 300 V | USB port: Yes | Surge protection: Yes | Non-operating altitude: 0 - 1500 m | Output operation voltage (max): 240 V | Weight: 14.4 kg | Battery recharge time: 4 h

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903