

CyberPower OLS1500EA uninterruptible power supply (UPS) Double-conversion (Online) 1.5 kVA 1350 W 4 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **OLS1500EA-DE** · EAN: **4711027790299** · Prekės kodas: **578600**



490,90 €

Kaina su PVM

Be PVM: **405,70 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Online (Double Conversion) UPS Topology
- ✓ Generator Compatible
- ✓ Zero Transfer Time
- ✓ Surge and Spike Protection
- ✓ Variable Speed Fans
- ✓ Emergency Power Off (EPO) Port
- ✓ SNMP/HTTP Remote Management Capability (Optional)
- ✓ ECO Mode
- ✓ Overload Protection



Aprašymas

CyberPower OLS1500EA is a high-performance UPS featuring online double-conversion topology, which provides seamless Pure Sine Wave power for mission-critical devices such as NAS and servers, DVRs/surveillance systems, transportation and infrastructure, and emergency systems. It's typically integrated in the back office, server room, and data center environment.

The UPS is designed with color LCD panel for users to monitor power system and configure settings easily. This model is generator compatible and also adopts ECO mode to conserve power. The product can be connected to Emergency Power Off (EPO) switch, which allows users to shut off UPS immediately during emergency. The variable speed fans provide automatic thermal management based on power load to reduce noise and provide greater comfort for users.

Techninė specifikacija

Specifications	
Sandėlio grupė	UPS power supplies [+106][-145]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	1.5 kVA
Output power	1350 W
Waveform	Pure sine
Input operation voltage (min)	190 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Maximum current	9 A
Surge energy rating	345 J
Response time	0 ms
Efficiency (ECO mode)	95%
Power factor	0.9
Input power factor	0.98
Output voltage Total Harmonic Distortion (THD)	5%
EMI/RFI noise filtering	Yes
Surge protection	Yes
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Battery replacement, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	IEC 320
Power plug	C13 coupler
AC outlets quantity	4 AC outlet(s)
Number of output IEC jumpers	2
USB port	Yes
USB 2.0 ports quantity	1
Emergency Power Off (EPO) connector	Yes

Battery

Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	5.3 min
Typical backup time at half load	15.3 min
Battery recharge time	4 h
Charging current	1.5 A

Design

Form factor	Tower
Product colour	Black
Housing material	Metal
Cable length	1.5 m
Display type	LCD

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	20 - 90%
Storage relative humidity (H-H)	10 - 90%
Operating altitude	0 - 1500 m
Non-operating altitude	0 - 1500 m

Certificates

Compliance certificates	CE
Certification	RoHS

Packaging content

Cables included	USB cable
Manual	Yes

Weight & dimensions

Width	151 mm
Depth	394 mm
Height	225 mm
Weight	14.4 kg

Packaging data

Package width	241 mm
Package depth	510 mm
Package height	313 mm

Package weight	16.2 kg
Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China
Matmenys ir svoris	
Matmenys (l × p × a)	51,00cm × 31,00cm × 24,00cm
Svoris	15,80kg