



**Switch TP-LINK  
Omada SG2218P  
Desktop/pedestal  
16x10Base-T  
100Base-TX  
1000Base-T  
2xSFP PoE+  
ports 16 150  
Watts SG2218P**

Modelis: SG2218P

Gamintojas: TP-LINK

EAN: 4897098689509

Prekės kodas: 578743

**260.98€**

TP-Link's brand new Omada smart switches provide huge upgrade comparing with previous versions. The switches can be managed by Omada SDN Controller, which provides professional and reliable one-step solutions. Integrated L2 and L2+ features such as 802.1Q VLAN, QoS, IGMP Snooping and static

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

routing

provide cost-effective networking solutions for small and medium-sized businesses without sacrificing

enhanced usability and strong performance.

- 16× Gigabit 802.3af/at PoE+ ports and 2× Gigabit SFP Slots
- 150 W total PoE budget with up to 30 W PoE output per port\*
- Centralized cloud management via the web or the Omada app†
- Standalone management via web, CLI, SNMP, and RMON
- Static Routing helps route internal traffic for higher efficiency
- VLAN, ACL, QoS, and IGMP Snooping
- Durable metal casing and rackmountable design

Summary: TP-Link Omada 18-Port Gigabit Smart Switch with 16-Port PoE+. Switch type: Managed, Switch layer: L2/L2+. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16. MAC address table: 8000 entries, Switching capacity: 26.78 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE.... Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: <https://www.tp-link.com/en/business-networking/omada-switch-poe/sg2218p/> | ARP inspection: Yes | Cloud-managed: Yes | Configuring Location Settings (CLI): Yes | MIB support: MIB II (RFC1213), Bridge MIB (RFC1493), P/Q-Bridge MIB (RFC2674), Radius Accounting Client MIB (RFC2620), Radius Authentication Client MIB (RFC2618), Remote Ping, Traceroute MIB (RFC2925), Support TP-Link private MIBs, RMON MIB(RFC1757, rmon 1,2,3,9) | Quality of Service (QoS) support: Yes | Switch layer: L2/L2+ | Switch type: Managed | System event log: Yes | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP module slots quantity: 2 | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Broadcast storm control: Yes | Ethernet LAN data rates: 10,100,1000 | Flow control support: Yes | IP routing: Yes | Link aggregation: Yes | Networking standards: IEEE 802.1D/IEEE 802.1p/IEEE 802.1Q/IEEE 802.1s/IEEE 802.1w/IEEE 802.1x/IEEE 802.3ab/IEEE 802.3ad/IEEE 802.3az/IEEE 802.3i/IEEE 802.3u/IEEE 802.3x/IEEE 802.3z | Policy-based routing: Yes | Rate limiting: Yes | Spanning tree protocol: Yes | VLAN support: Yes | Forwarding rate: 26.78 | Jumbo frames: 9 | Jumbo frames support: Yes | MAC address table: 8000 | Packet buffer memory: 4.1 | Switching capacity: 26.78 | Access Control List (ACL): Yes | Authentication: MAC-based authentication, Port-based authentication | BPDU filtering/protection: Yes | DHCP features: DHCP

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shoppro.lt](http://www.shoppro.lt) | [info@shoppro.lt](mailto:info@shoppro.lt) | +370 693 39903

client/DHCP relay/DHCP snooping | Loop protection: Yes | MAC address filtering: Yes | SSH/SSL support: Yes | Static port security: Yes | Multicast features: Multicast forwarding | Multicast support: Yes | Form factor: 1U | LED indicators: Yes | Product colour: Black | Rack mounting: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Power consumption (max): 181.4 | Power source: DC/PoE | Power supply included: Yes | Power over Ethernet (PoE): Yes | Total Power over Ethernet (PoE) budget: 150 | Heat dissipation: 619.06 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 50 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 180 | Height: 44 | Width: 440 | Cables included: LAN (RJ-45) | User guide: Yes | Package type: Box | Certification: CE, FCC, RoHS | Series: Omada | Model name: SG2218P | Units per Shipping Box: 6 | Unit Calculated Volume: 0.01287 | Unit Calculated Weight: 3.42