

Power Supply ENDORFY SUPREMO FM6 100 - 240 V 1000 W EY7A011

Gamintojas: **ENDORFY** · Modelis: **EY7A011** · EAN: **5903018667942** · Prekės kodas: **578765**



142,90 € ~~164,90 €~~

Kaina su PVM

Be PVM: **118,10 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Supremo FM6 1000 W is a fully modular modern ATX 3.1-compliant power supply unit, providing stable operation and supporting PCIe 5.1 GPUs. 80 PLUS® Gold certificate confirms its high efficiency, while a Fluctus fan guarantees quiet work. Thanks to the Japanese capacitors and a 10-year warranty, it's a reliable solution for avid gamers and professionals alike.

Supremo FM6 1000 W

Supremo FM6 1000 W is a modular ATX 3.1 PSU for demanding users that supports PCIe 5.1 graphics cards. It boasts high power efficiency confirmed by an 80 PLUS® Gold certificate. The power supply's design utilizes only the Japanese capacitors that guarantee its long service life.

The quiet Fluctus 120 mm fan and optimized component placement ensure low temperatures with almost noiseless operation. Additionally, the modular cables make it easier to keep the surrounding space in order. The PSU also has a security package that protects it from overloading and power surges. Its quality is additionally confirmed by a 10-year warranty.

Ready for latest ATX 3.1 standards

Supremo FM6 1000 W is a power supply unit compliant with the ATX 3.1 standard. Its major advantages include even better performance, stability, and resistance to momentary power spikes than previous ATX standards. The set includes the 12V-2x6 cable fully compatible with PCIe 5.1 cards. A traditional PCI-E 6+2 PIN splitter is also included to handle GPUs with classic power supply systems.

80 PLUS® Gold - supreme performance and reliability

The 80 PLUS® Gold certificate confirms the high efficiency of the Supremo FM6 1000 W power supply unit. Thanks to its excellent quality and refined design, the unit is characterized by low-noise and low-temperature operation, resulting in its extended service life.

Silence first

Supremo FM6 1000 W has been designed with maximum user comfort in mind. Thanks to the optimized component setup streamlining the air flow and a high-performance cooling system, the PSU runs exceptionally quietly and retains low temperature even under full load.

Premium class capacitors made in Japan

All capacitors installed in the Supremo FM6 1000 W power supply unit are reliable, premium-class components made in Japan. They retain their operating parameters even at high temperatures (105 °C), enabling them to perform faultlessly and stably for years to come, even under extremely demanding operating conditions.

Summary: ENDORFY Supremo FM6 1000 W. Total power: 1000 W, AC input voltage: 100 - 240 V, AC input frequency: 50/60 Hz. Motherboard power connector: 24-pin ATX, Motherboard power cable length: 60 cm, SATA power cable length: 560,720,880 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Cables included: AC | Vendor Homepage: <https://endorfy.com/en/product/supremo-fm6-850-w/> | Bendroji galia: 1000 | AC įėjimo įtampa: 100 - 240 | AC įėjimo dažnis: 50/60 | Įvesties srovė: 13 - 6.5 | Galios koeficiento pataisos (PFC) tipas: Aktyvus | Kompleksinė galia (+3,3 V): 100 | Kompleksinė galia (+12 V): 996 | Kompleksinė galia (+5V): 100 | Kompleksinė galia (-12 V): 3.6 | Kompleksinė galia (+5 VSB): 15 | Didžiausia išėjimo įtampa (+3,3 V): 20 | Didžiausia išėjimo įtampa (+12 V): 83 | Didžiausia išėjimo įtampa (+5 V): 20 | Didžiausia išėjimo įtampa (-12 V): 0.3 | Didžiausia išėjimo įtampa (+12 VSB): 3 | Maitinimo apsaugos ypatybės: Apsauga nuo per didelės įtampos/Minimaliosios įtampos apsauga/Per žema temperatūra/Surge & inrush protection (SIP)/Trumpasis jungimas/Viršijus galią/Viršijus nuolatinę srovę | Motininės plokštės maitinimo jungtis: 24-pin ATX | Motininės plokštės maitinimo kabelio ilgis: 600 | SATA elektros jungčių skaičius: 8 | SATA maitinimo kabelio ilgis: 560/720/880 | SATA maitinimo kabelių skaičius: 3 | Periferinė (Molex) galios jungtis (4-pin): 1 | Periferinio („Molex“) maitinimo kabelio ilgis: 880 | EPS maitinimo jungtis (8-kaisčiai): Taip | EPS maitinimo jungtis (4 + 4 kontaktai): Taip | PCI „Express“ maitinimo jungtis (6 + 2 kontaktai): 3 | „PCI Express“ maitinimo jungtis (12 + 4 kaištinių kontaktų): 1 | PCI „Express“ galia kabelio ilgis: 560 | Perdavimo laidų tipas: Visiškai modulinis | Sertifikatas 80 PLUS: 80 PLUS Gold | „Cybenetics“ sertifikavimas: Platina | Paskirtis: PC | Maitinimo bloko (PSU) formos koeficientas: ATX | ATX versija: 3.1 | Aušinimo padengimo tipas: FDB | Vidutinis laikas tarp triukščių (MTBF): 100000 | Produkto spalva: Juoda | Aušinimo tipas: Aktyvus | Ventilatoriaus skersmuo: 120 | Ventilatorių skaičius: 1 | Ventilatoriaus vieta: Viršus | Iluminacija: Ne | LED indikatoriai: Ne | On/off mygtukas: Taip | Ventilatoriaus įjungimo ir išjungimo jungiklis: Ne | Pridėti kabeliai: AC | Atitikties sertifikatai: CB/CCC/CE/Federalinė ryšių komisija (FCC)/RoHS/UKCA | Plotis: 140 | Ilgis: 150 | Aukštis: 87 | Instrukcija: Taip | Pakuotės plotis: 220 | Pakuotės gylis: 270 | Pakuotės aukštis: 95 | Paketo svoris: 2740 | Pakuotės tipas: „Box“ | Sudėtyje nėra: Gyvsidabris/Kadmis/Švinas | Tvarumo sertifikatai: ErP | Garantinis laikotarpis: 10 | Bruto svoris: 2.8 | Neto svoris: 2 | Vienetų skaičius vienoje siuntimo dėžėje: 1 | Vieneto plotis: 27 | Shipping Box Height: 22 | Vieneto gylis: 10 | Vieneto aukštis: 22 | Name: CASE PSU ATX3.1 1000W/SUPREMO FM6 EY7A011 ENDORFY | Model name: Supremo FM6 1000 W

Techninė specifikacija

Matmenys ir svoris

Matmenys (l × p × a) 10,00cm × 27,00cm × 22,00cm

Svoris 1,50kg