



**Power Supply**  
**GIGABYTE**  
**UD750GM PG5**  
**V2 ATX 3.1 750**  
**Watts Efficiency**  
**80 PLUS GOLD**  
**PFC Active MTBF**  
**100000 hours**  
**GP-**  
**UD750GMPG5V2**

Modelis: GP-UD750GM PG5 V2

Gamintojas: GIGABYTE

EAN: 4719331555870

Prekės kodas: 578823

**94.99€**

Ensure reliable and efficient power delivery with GIGABYTE power supplies. Designed for peak performance and durability, our PSUs offer stable and consistent energy to power your high-performance systems. With advanced protections and high-quality components, GIGABYTE power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

supplies provide the confidence you need for seamless, uninterrupted computing experiences.

- Intel ATX 3.1 and PCIe Gen 5.1 ready
- 80 PLUS Gold certified
- Fully modular design
- Powerful single +12V rail
- Compact size
- 100% Japanese capacitors
- 120mm smart hydraulic bearing (HYB) fan
- Optimized thermal solution
- OVP/OPP/SCP/UVP/OCP/OTP protection

Summary: GIGABYTE UD750GM PG5 V2 Power Supply Unit- PCIe Gen 5.1, 80 PLUS Gold, Fully Modular Design, 120mm Fan, ATX 3.1 compatible, EU Plug. Total power: 750 W, AC input voltage: 100 - 240 V, AC input frequency: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 61 cm, SATA power cable length: 150,600 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 150 mm, Depth: 140 mm, Height: 86 mm | Vendor Homepage: <https://www.gigabyte.com/Power-Supply/GP-UD750GM-PG5-V2#kf> | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Combined power (+12V): 750 | Combined power (+3.3V): 105 | Combined power (+5V): 105 | Combined power (+5Vsb): 15 | Combined power (-12V): 3.6 | Efficiency: 90 | Hold time: 16 | Input current: 12 - 6.5 | Max output current (+12V): 62.5 | Max output current (+3.3V): 20 | Max output current (+5V): 20 | Max output current (+5Vsb): 3 | Max output current (-12V): 0.3 | Power factor: 0.9 | Power Factor Correction (PFC) type: Active | Power protection features: Over current/Over power/Over voltage/Overheating/Short circuit/Under voltage | Total power: 750 | Cabling type: Fully-Modular | CPU power cable length: 650 | CPU power connector (4+4 pin): Yes | Floppy drive power connector: 1 | Motherboard power cable length: 610 | Motherboard power connector: 20+4 pin ATX | Number of EPS connectors: 2 | Number of SATA power connectors: 8 | PCI Express connector: Yes | PCI Express power cable length: 600 | PCI Express power connectors (12+4 pin): 1 | PCI Express power connectors (12+4 pin) cable length: 700 | PCI Express power connectors (6+2 pin): 4 | Peripheral (Molex) power cable length: 150/500 | Peripheral (Molex) power connectors (4-pin): 3 | SATA power cable length: 150/600 | 80 PLUS certification: 80 PLUS Gold | ATX version: 3.1 | Bearing technology: HYB | Mean time between failures (MTBF): 100000 | Power supply unit (PSU) form factor: ATX | Purpose: PC | Cooling type: Active | Fan diameter: 120 | Number of fans:

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

1 | On/off switch: Yes | Product colour: Black | Depth: 140 | Height: 86 | Weight: 2340 | Width: 150 |  
Package depth: 269 | Package height: 211 | Package type: Box | Package weight: 2500 | Package  
width: 618 | Warranty period: 5 | Model name: UD750GM PG5 V2 | Units per Pallet: 0 | Units per  
Shipping Box: 5 | Unit Calculated Volume: 0.007812 | Unit Calculated Weight: 2.5