



Power Supply ASROCK ATX PC 100 - 240 V 750 W PRO-750B

Modelis: PRO-750B

Gamintojas: ASROCK

EAN: 4711581491724

Prekės kodas: 578862

63.98€

Native PCIe 12V-2x6 Cable

Dual Color Design

With ASRock Classic Green connectors, users can easily see if the connector has been plugged properly.

80 PLUS CERTIFIED

The PRO series is created for value-focused users, offering 80 PLUS Bronze models in 850W, 750W, and 650W options.

Safety First with ASRock

Full suite of protections to keep all components safe during normal to extreme power levels.

ASRock offers an outstanding 3 -Year warranty, guaranteeing long term reliable and peace of mind

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

operation.

- 80 PLUS® BRONZE Certified
- ATX3.1 & PCIe5.1 Ready
- Native 12V-2x6 Connector Dual Color Design (450W)
- Low noise 120mm FAN

Summary: Asrock PRO-750B. Total power: 750 W, AC input voltage: 100 - 240 V, AC input frequency: 50/60 Hz. Motherboard power connector: 24-pin ATX, Motherboard power cable length: 60 cm, SATA power cable length: 450,570,690 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 150 mm, Depth: 140 mm, Height: 86 mm | Vendor Homepage:

<https://www.asrock.com/Power-Supply/PRO/PRO-750B> | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Input current: 10 - 5 | Max output current (+12V): 62.5 | Power protection features: Over current/Over power/Over voltage/Overheating/Short circuit/Under voltage | Total power: 750 | Cabling type: Non-Modular | CPU power connector (4+4 pin): Yes | EPS power connector (4+4 pin): Yes | Motherboard power cable length: 600 | Motherboard power connector: 24-pin ATX | Number of SATA power cables: 2 | Number of SATA power connectors: 4 | PCI Express power connectors (12+4 pin): 1 | PCI Express power connectors (6+2 pin): 2 | Peripheral (Molex) power connectors (4-pin): 2 | SATA power cable length: 450/570/690 | 80 PLUS certification: 80 PLUS Bronze | ATX version: 3.1 | Mean time between failures (MTBF): 100000 | Power supply unit (PSU) form factor: ATX | Purpose: PC | Cooling type: Active | Fan diameter: 120 | Illumination: No | Number of fans: 1 | On/off switch: Yes | Product colour: Black | Depth: 140 | Height: 86 | Width: 150 | Package type: Box | Warranty period: 3 | Model name: PRO-750B | Units per Pallet: 0 | Units per Shipping Box: 6 | Unit Calculated Volume: 0.006526 | Unit Calculated Weight: 2.08