



Power Supply XILENCE Performance C+ XP750R6.2 XN430

Modelis: XN430

Gamintojas: XILENCE

EAN: 4044953503573

Prekės kodas: 578868

58.99€

The C+Series is a power supply series with the ATX standard 2.52 and black ribbon cables. The power supplies are designed for office and home computers, but can also be installed in PCs that are occasionally used for gaming.

The black design of the power supplies and the elegant flat ribbon cables blend visually into any PC build. The power supplies deliver stable voltages with high efficiency (80+ Standard) to meet the ErP2014 standard. The integrated black 120mm fan provides silent cooling. Four integrated safety circuits ensure safe operation at all times.

Summary: Xilence XP750R6.2. Total power: 750 W, AC input voltage: 200 - 240 V, AC input frequency: 50 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 50 cm, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm | Vendor

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Homepage: <https://www.xilence.net/en/power-supplies/243> | AC input frequency: 50 | AC input voltage: 200 - 240 | Input current: 10 | Max output current (+12V1): 58 | Max output current (+3.3V): 24 | Max output current (+5V): 18 | Max output current (+5Vsb): 2.5 | Max output current (-12V): 0.5 | Power Factor Correction (PFC) type: Active | Power protection features: Over current/Over power/Over voltage/Short circuit/Under voltage | Total power: 750 | Cabling type: Non-Modular | Motherboard power cable length: 500 | Motherboard power connector: 20+4 pin ATX | Number of PATA power connectors: 3 | Number of SATA power connectors: 5 | PCI Express power connectors (6+2 pin): 2 | 80 PLUS certification: 80 PLUS Gold | Bearing technology: Hypro Bearing | Power supply unit (PSU) form factor: ATX | Purpose: PC | Cooling type: Active | Fan diameter: 120 | Number of fans: 1 | Product colour: Black | Model name: Performance C+ | XP750R6.2 | Units per Pallet: 0 | Units per Shipping Box: 8 | Unit Calculated Volume: 0.006593 | Unit Calculated Weight: 1.92