

XPG PYLON II 650w BROZNZE Power Supply

Gamintojas: **ADATA** · Modelis: **PYLON650IIB-BKCEU** · EAN: **4711658150868** · Prekės kodas: **578887**



56.89€

Kaina su PVM

Be PVM: 47.02€

In Stock




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 650 W 100 - 240 V 50/60 Hz
- ✓ Motherboard power connector: 24-pin ATX
- ✓ PC ATX 80 PLUS Bronze
- ✓ Active 13.5 cm 0 - 2300 RPM
- ✓ Black



Aprašymas

PYLON II UNLEASH THE SURGE

The PYLON II Bronze PSU delivers 80 PLUS Bronze efficiency, cutting energy costs without sacrificing performance. Designed to meet Intel ATX 3.1 standards, it offers a future-ready solution for high-demand components. Equipped with a quiet and durable FDB fan, it ensures efficient cooling for a stable and noise-free experience. Backed by 8 industrial-grade protections and a 5-year warranty, the PYLON II guarantees long-term reliability and peace of mind for your build.

Intel ATX 3.1 Compliant, Future-Ready Design

Designed with the latest Intel ATX 3.1 standards, the PYLON II is equipped with 12V-2x6 connector*, ensuring compatibility with high-performance components. It's engineered to meet the evolving needs of modern systems.

Quiet, Efficient Cooling with FDB Fan

Equipped with a 135mm FDB fan, the PYLON II ensures quiet operation and long-lasting durability. It keeps your system cool even under demanding workloads, delivering optimal cooling without compromising on noise levels.

Comprehensive Protection for Peace of Mind

With 8 industrial-grade protections, the PYLON II shields your system from power surges, short circuits, and other potential risks. This protection, combined with a 5-year warranty, offers long-term peace of mind.

Techninė specifikacija

Power	
Total power	650 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	10 A
Power factor	0.99
Power Factor Correction (PFC) type	Active
Max output current (+3.3V)	20 A
Max output current (+12V)	54 A
Max output current (+5V)	20 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	3 A
Power protection features	No load operation, Over current, Over power, Over voltage, Overheating, Short circuit, Surge & inrush, Under voltage
Ports & interfaces	
Motherboard power connector	24-pin ATX
Peripheral (Molex) power connectors (4-pin)	2
Number of SATA power connectors	6
EPS power connector (8-pin)	Yes
PCI Express power connectors (6+2 pin)	1
Performance	
Purpose	PC
Power supply unit (PSU) form factor	ATX
80 PLUS certification	80 PLUS Bronze
ATX version	3.1
Bearing technology	FDB

Mean time between failures (MTBF) 100000 h

Design

Product colour	Black
Cooling type	Active
Fan diameter	13.5 cm
Number of fans	1 fan(s)
Fan speed	0 - 2300 RPM
On/off switch	Yes

Weight & dimensions

Width	150 mm
Depth	150 mm
Height	86 mm
Weight	1.8 kg

Matmenys ir svoris

Matmenys (l × P × A)	30.00cm × 12.00cm × 21.00cm
----------------------	-----------------------------

Dokumentai ir vaizdo įrašai

- › [User manual](#)
- › [Product leaflet](#)

Gamintojo ir saugos informacija

MANUFACTURER

ADATA Technology Co., Ltd.

Liancheng Rd., Zhonghe Dist. No.258, 235 New Taipei City, TW
xpg.com

EU RESPONSIBLE PERSON

ADATA Technology Co., Ltd.

Landsberger Strasse 302, 80687 Munich, DE
xpg.com

DISTRIBUTOR

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt