



TP-Link Omada 16-Port Gigabit Smart Switch with 2 SFP Slots



Modelis: TL-SG2218

Gamintojas: TP-LINK

EAN: 1210002611824

Prekės kodas: 579601

168.99€

Certification: CE, FCC, RoHS | Web-based management: Yes | Product colour: Black | DHCP features: DHCP client | DHCP features: DHCP relay | Multicast support: Yes | AC input voltage: 100 - 240 V | DHCP features: DHCP server | LED indicators: Yes | Depth: 180 mm | Flow control support: Yes | Switch layer: L2/L2+ | System event log: Yes | DHCP features: DHCP snooping | Power source: AC | Storage relative humidity (H-H): 5 - 90% | Form factor: 1U | Access Control List (ACL): Yes | Networking standards: IEEE 802.3i | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power supply included: Yes | DHCP features: DHCPv6 snooping | Power consumption (max): 12.3 W | 10G support: No | Quick start guide: Yes | Heat dissipation: 41.97 BTU/h | AC input frequency: 50/60 Hz | Networking standards: IEEE 802.3z | Package width: 250 mm | Networking standards: IEEE 802.3ab | Operating temperature (T-T): 0 - 40 °C | Switch type: Managed | Operating relative humidity (H-H): 10 - 90% | Loop protection: Yes | Static route: Yes | Networking standards: IEEE 802.3u | MIB support: Yes | DHCP features: DHCPv6 client | Cables included: LAN (RJ-45) | Basic switching RJ-45 Ethernet ports quantity: 16 | Package weight: 2.45 kg | Height: 44 mm | SSH/SSL support: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Package depth: 528 mm | Virtual LAN features: Voice VLAN | Ethernet LAN data rates: 10,100,1000 Mbit/s | IGMP snooping: Yes | Rack mounting: Yes | ARP inspection: Yes | MAC address table: 8000 entries | Harmonized System (HS) code: 85176990 | Virtual LAN features: Tagged VLAN | Power over Ethernet (PoE): No | Width: 440 mm | Virtual LAN features: Protocol-based VLAN | Number of VLANs: 4000 | Number of IP interfaces: 16 | VLAN support: Yes | Package height: 80 mm | BPDU filtering/protection: Yes | Virtual LAN features: Port-based VLAN | Forwarding rate: 26.8 Mpps | Number of static routes: 32 | Switching capacity: 36 Gbit/s | Cables included: AC | Rate limiting: Yes | Virtual LAN features: Private VLAN | Packet buffer memory: 4.1 MB | Port mirroring: Yes | GARP VLAN Registration Protocol (GVRP): Yes | Gigabit Ethernet (copper) ports quantity: 16 | Link aggregation: Yes | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | Cloud-managed: Yes | Management protocols: SNMPv1/v2c/v3, SNTP | Fanless: Yes | Store-and-forward: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | Jumbo frames support: Yes | SFP module slots quantity: 2