

TP-Link Omada 16-Port Gigabit Smart Switch with 2 SFP Slots

Gamintojas: **TP-LINK** · Modelis: **TL-SG2218** · EAN: **1210002611824** · Prekės kodas: **579601**



161,90 €

Kaina su PVM

Be PVM: **133,80 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Certification: CE, FCC, RoHS | Product colour: Black | Web-based management: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | Rate limiting: Yes | Power over Ethernet (PoE): No | Width: 440 mm | SFP module slots quantity: 2 | Power supply included: Yes | Virtual LAN features: Private VLAN | Height: 44 mm | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3i | Cables included: LAN (RJ-45) | Package height: 80 mm | AC input voltage: 100 - 240 V | Power source: AC | Basic switching RJ-45 Ethernet ports quantity: 16 | BPDU filtering/protection: Yes | Form factor: 1U | Virtual LAN features: Protocol-based VLAN | DHCP features: DHCP snooping | Access Control List (ACL): Yes | LED indicators: Yes | Switch layer: L2/L2+ | System event log: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | DHCP features: DHCP server | DHCP features: DHCPv6 client | Package width: 250 mm | Operating relative humidity (H-H): 10 - 90% | DHCP features: DHCPv6 snooping | AC input frequency: 50/60 Hz | Rack mounting: Yes | DHCP features: DHCP client | DHCP features: DHCP relay | Switch type: Managed | Depth: 180 mm | Virtual LAN features: Tagged VLAN | 10G support: No | Number of VLANs: 4000 | Package depth: 528 mm | SSH/SSL support: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | VLAN support: Yes | Networking standards: IEEE 802.3u | MIB support: Yes | Loop protection: Yes | Flow control support: Yes | Cables included: AC | Operating temperature (T-T): 0 - 40 °C | Package weight: 2.45 kg | Static route: Yes | IGMP snooping: Yes | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.3z | Harmonized System (HS) code: 85176990 | Switching capacity: 36 Gbit/s | Virtual LAN features: Port-based VLAN | Multicast support: Yes | Heat dissipation: 41.97 BTU/h | Management protocols: SNMPv1/v2c/v3, SNMP | Packet buffer memory: 4.1 MB | Port mirroring: Yes | Store-and-forward: Yes | MAC address table: 8000 entries | Jumbo frames support: Yes | Gigabit Ethernet (copper) ports quantity: 16 | ARP inspection: Yes | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | Virtual LAN features: Voice VLAN | Spanning tree protocol: Yes | Jumbo frames: 9000 | Forwarding rate: 26.8 Mpps | Power consumption (max): 12.3 W | Quick start guide: Yes | Fanless: Yes | Link aggregation: Yes | Number of IP interfaces: 16 | Number of static routes: 32 | GARP VLAN Registration Protocol (GVRP): Yes | Cloud-managed: Yes

Techninė specifikacija

Specifications	
Sandėlio grupė	Switches [+96][-66]
Matmenys ir svoris	
Matmenys (I × P × A)	28,00cm × 8,00cm × 53,00cm
Svoris	2,85kg