



TP-Link Tapo C615G KIT Dome IP security camera Outdoor 2304 x 1296 pixels Ceiling/Wall/Pole

Modelis: Tapo C615G KIT

Gamintojas: TP-LINK

EAN: 8885020629705

Prekės kodas: 579606

120.99€

Audio system: 2-way | AC input voltage: 100 - 240 V | Compliance certificates: CE | Compliance certificates: RCM | Connectivity technology: Wireless | Bluetooth: No | AC input frequency: 50/60 Hz | Reset button: Yes | Product colour: White | Intelligent Video Surveillance (IVS) system features: Vehicle detection | Intelligent Video Surveillance (IVS) system features: Human detection | Battery capacity: 6700 mAh | Intelligent Video Surveillance (IVS) system features: Pet detection | Mobile network generation: 4G | Rechargeable battery: Yes | Lens viewing angle, horizontal: 84.4° | Drilling template included: Yes | Day/night mode: Yes | Cloud-managed: Yes | Number of lenses: 1 | Lens viewing angle, vertical: 44.3° | Placement supported: Outdoor | Night vision: Yes | Mounting type: Ceiling/Wall/Pole | Video motion detection: Yes | Fixed focal length: 4 mm | SIM card type: NanoSIM |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

SIM card slot: Yes | 4G standard: LTE-TDD & LTE-FDD | Sensor type: CMOS | LED type: IR | Camera tilt control: Yes | Camera pan control: Yes | Number of cameras: 1 | Built-in light: Yes | Built-in speaker(s): Yes | Mounting kit: Yes | Mobile network connection: Yes | Maximum aperture number: 1.6 | Auto-tracking: Yes | Power source type: AC, Battery, Solar | Built-in HDD: No | Noise reduction technology: 3D noise reduction | Card reader integrated: Yes | Built-in microphone: Yes | Weight: 451 g | International Protection (IP) code: IP65 | Digital zoom: 10.8x | Infra-red wavelength: 850 nm | Maximum memory card size: 512 GB | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN: No | Depth: 116.1 mm | Battery technology: Lithium-Ion (Li-Ion) | Progressive scan: Yes | Maximum resolution: 2304 x 1296 pixels | Form factor: Dome | Height: 84.1 mm | Wide Dynamic Range (WDR): Yes | Width: 130.9 mm | Storage temperature (T-T): -40 - 60 °C | Operating temperature (T-T): -20 - 45 °C | Compatible memory cards: MicroSD (TransFlash) | DC output voltage: 5 | Zoom capability: Yes | Wi-Fi: No | Total megapixels: 3 MP | Optical sensor size: 25.4 / 2.8 mm (1 / 2.8") | Noise reduction: Yes | Security algorithms: SSL/TLS | Type: IP security camera | Siren noise level: 98.6 dB | Built-in siren: Yes | Lens viewing angle, diagonal: 100.6° | Storage relative humidity (H-H): 0 - 90%