



**Wireless Router
TP-LINK TL-
MR100-
OUTDOOR Wi-Fi
4 (802.11n)
Data speed 300
Mbit/s Ethernet
WAN Yes DSL
WAN Yes SIM
card slot Yes
WAN connection
type RJ-45
Ethernet LAN
Yes 3G Yes 4G
Yes 1xLAN ports
TL-MR100-
OUTDOOR**

Modelis: TL-MR100-OUTDOOR

Gamintojas: TP-LINK

EAN: 1210002601641

Prekės kodas: 579675

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

78.99€

TP-LINK TL-MR100

300 Mbps Wireless N 4G LTE Router

Cutting-edge 4G network

Share internet access with up to 32 Wi-Fi devices and enjoy download speeds of up to 150 Mbps

TL-MR100-Outdoor

4G 300 Mbps Wi-Fi Outdoor Router

- 4G LTE and Fast Wi-Fi Speed : supports LTE up to 150 Mbps and Wi-Fi up to 300 Mbps on 2.4 GHz .*
- Durable Outdoor Enclosure: Robust outdoor connectivity and reliability with IP65 weatherproof protection** and $\pm 6\text{kV}$ lightning protection & $\pm 15\text{kV}$ ESD protection[§].
- Multiple Mounting Installation: Install easily anywhere with pole, wall, or window mounting for flexible, convenient use.
- PoE/DC Power Supply: Supports 802.3af and passive PoE, enabling easy deployment.
- Plug and Play: Plug in a SIM card to get instant internet access anywhere.
- Simplified Setup: Easily set up and manage your network with the Tether app.

Vendor Homepage: <https://www.tp-link.com/uk/home-networking/5g-4g-router/tl-mr100-outdoor/#overview> | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Wi-Fi band: Single-band (2.4 GHz) | Wi-Fi standards: 802.11b/802.11g/Wi-Fi 4 (802.11n) | WLAN data transfer rate (max): 300 | 3G/4G USB modem compatibility: No | DSL WAN: Yes | Ethernet WAN: Yes | SIM card slot: Yes | WAN connection type: RJ-45 | Cabling technology: 10/100Base-T(X) | Dynamic DNS (DDNS): Yes | Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11n): 20 | Ethernet LAN: Yes | Ethernet LAN interface type: Fast Ethernet | Networking standards: IEEE 802.11b/IEEE 802.11g/IEEE 802.11n | Port forwarding: Yes | Port triggering: Yes | Receiver sensitivity: 11g 54M: -74 dBm 11n HT20: -73 dBm 11n HT40: -70 dBm | Wireless radio: Yes | 3G: Yes | 3G bands supported: 2100/850/900 | 3G standards: HSPA/HSPA+/UMTS | 4G: Yes | 4G bands supported: 1800/2100/2600/700/800/850/900 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

4G standard: LTE-TDD & LTE-FDD | Mobile network generation: 4G | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 1 | USB port: No | Reset button: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Wireless statistics: Yes | DMZ support: Yes | Firewall: Yes | Guest access: Yes | IP address filtering: Yes | MAC address filtering: Yes | Schedule access: Yes | Security algorithms: WPA/WPA2/WPA2-PSK/WPA-PSK | Stateful Packet Inspection (SPI): Yes | DHCP client: Yes | DHCP server: Yes | Supported network protocols: IPv4, IPv6 | Universal Plug and Play (UPnP): Yes | International Protection (IP) code: IP65 | On/off switch: Yes | Product colour: White | Wall mountable: Yes | Cables included: LAN (RJ-45) | Certification: CE, RoHS | Mounting kit: Yes | PoE injector included: Yes | Quick installation guide: Yes | Antenna design: External | Antennas quantity: 2 | Firmware upgradeable: Yes | Output current: 1 | Output voltage: 12 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) voltage: 48 | Power source type: DC,PoE | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -30 - 60 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 100 | Height: 54.7 | Width: 226.6 | Model: TL-MR100-Outdoor | Model name: TL-MR100-OUTDOOR | Units per Pallet: 0 | Units per Shipping Box: 12 | Unit Calculated Volume: 0.006589 | Unit Calculated Weight: 1.39