

TP-Link TL-MR100-OUTDOOR wireless router Fast Ethernet Single-band (2.4 GHz) 4G White

Gamintojas: **TP-LINK** · Modelis: **TL-MR100-OUTDOOR** · EAN: **1210002601641** · Prekės kodas: **579675**



86,90 €

Kaina su PVM

Be PVM: **71,82 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4G LTE and Fast Wi-Fi Speed : supports LTE up to 150 Mbps and Wi-Fi up to 300 Mbps on 2.4 GHz .*
- ✓ Durable Outdoor Enclosure: Robust outdoor connectivity and reliability with IP65 weatherproof protection** and ±6kV lightning protection & ±15kV ESD protection§
- ✓ Multiple Mounting Installation: Install easily anywhere with pole, wall, or window mounting for flexible, convenient use
- ✓ PoE/DC Power Supply: Supports 802.3af and passive PoE, enabling easy deployment
- ✓ Plug and Play: Plug in a SIM card to get instant internet access anywhere
- ✓ Simplified Setup: Easily set up and manage your network with the Tether app



Aprašymas

Dependable 4G Wi-Fi Internet Connectivity

The TL-MR100-Outdoor supports 4G LTE for internet download speeds up to 150 Mbps, paired with fast Wi-Fi speeds of up to 300 Mbps, enabling seamless networking experience.

Durable Outdoor Design for Stable Performance

Engineered for extreme environments, TL-MR100-Outdoor features IP65 waterproofing, operates from -30°C to 60°C, and 6kV lightning & 15kV ESD protection. Maintains uninterrupted connectivity in harsh weather conditions, delivering stable outdoor network performance.

Versatile Installation for Diverse Environments

The TL-MR100-Outdoor offers versatile installation options—mount on a pole or a wall, or adhesive to a window. This flexibility allows for installation in a wide range of environments, from urban areas to rural settings. Easily find the best location for optimal signal, ensuring reliable connectivity.

PoE/DC Power Support: Simplified Outdoor Setup

The TL-MR100-Outdoor features PoE and DC power supply, simplifying outdoor setup with flexible power options and ensuring reliable connectivity in diverse outdoor environments.

Easy Setup and Management

Set up TL-MR100-Outdoor in minutes thanks to its intuitive web interface and the powerful Tether app. Tether also lets you manage its network settings from any Android or iOS device, including parental controls and access control.

Techninė specifikacija

Specifications	
Sandėlio grupė	3G/4G Routers [+0][-0]
WAN connection	
Ethernet WAN	Yes
DSL WAN	Yes
SIM card slot	Yes
3G/4G USB modem compatibility	No
WAN connection type	RJ-45
Wireless LAN features	
Wi-Fi band	Single-band (2.4 GHz)
Top Wi-Fi standard	Wi-Fi 4 (802.11n)
WLAN data transfer rate (max)	300 Mbit/s
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Network	
Ethernet LAN	Yes
Ethernet LAN interface type	Fast Ethernet
Ethernet LAN data rates	100 Mbit/s
Cabling technology	10/100Base-T(X)
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Port forwarding	Yes
Port triggering	Yes
Dynamic DNS (DDNS)	Yes
Wireless radio	Yes
Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11n)	20 dBmW

Receiver sensitivity	11g 54M: -74 dBm 11n HT20: -73 dBm 11n HT40: -70 dBm
Mobile network	
Mobile network generation	4G
3G	Yes
4G	Yes
3G standards	HSPA, HSPA+, UMTS
4G standard	LTE-TDD & LTE-FDD
4G bands supported	700,800,850,900,1800,2100,2600 MHz
3G bands supported	850,900,2100 MHz
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
USB port	No
DC-in jack	Yes
Management features	
Wi-Fi Multimedia (WMM)/(WME)	Yes
Wireless statistics	Yes
Reset button	Yes
Security	
Security algorithms	WPA, WPA-PSK, WPA2, WPA2-PSK
Firewall	Yes
Guest access	Yes
Stateful Packet Inspection (SPI)	Yes
Schedule access	Yes
MAC address filtering	Yes
IP address filtering	Yes
DMZ support	Yes
Protocols	
DHCP client	Yes
DHCP server	Yes
Universal Plug and Play (UPnP)	Yes
Supported network protocols	IPv4, IPv6
Design	
Product colour	White
Wall mountable	Yes

International Protection (IP) code	IP65
On/off switch	Yes
Certificates	
Certification	CE, RoHS
Packaging content	
Cables included	LAN (RJ-45)
PoE injector included	Yes
Mounting kit	Yes
Quick installation guide	Yes
Antenna	
Antenna design	External
Antennas quantity	2
Features	
Firmware upgradeable	Yes
Power	
Power source type	DC, PoE
Output voltage	12 V
Output current	1 A
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) voltage	48 V
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	226.6 mm
Depth	100 mm
Height	54.7 mm
Matmenys ir svoris	
Matmenys (I × P × A)	28,00cm × 24,00cm × 8,00cm