



GIGABYTE UD1000GM PG5 V2 Power Supply Unit- PCIe Gen 5.1, 80 PLUS Gold, Fully Modular Design, 120mm Fan, ATX 3.1 compatible, EU Plug

Modelis: GP-UD1000GM PG5 V2

Gamintojas: GIGABYTE

EAN: 4719331556112

Prekės kodas: 579848

125.99€

Number of EPS connectors: 2 | PCI Express power connectors (16-pin): 1 | Package type: Box | AC input voltage: 100 - 240 V | Input current: 15 - 6.5 A | Package height: 211 mm | Product colour: Black | Package depth: 269 mm | Peripheral (Molex) power connectors (4-pin): 3 | Package weight:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

2.64 kg | Weight: 2.48 kg | Width: 150 mm | AC input frequency: 50/60 Hz | Cooling type: Active | Package width: 618 mm | ATX version: 3.1 | PCI Express power cable length: 70 cm | Peripheral (Molex) power cable length: 120 | Motherboard power connector: 20+4 pin ATX | Peripheral (Molex) power cable length: 500 mm | Power supply unit (PSU) form factor: ATX | Combined power (+3.3V): 125 W | Max output current (+12V): 83.3 A | Number of SATA power connectors: 8 | Combined power (-12V): 3.6 W | Motherboard power cable length: 61 cm | Floppy drive power connector: 1 | Hold time: 16 ms | Max output current (+5Vsb): 3 A | Total power: 1000 W | Cabling type: Fully-Modular | PCI Express power connectors (6+2 pin): 4 | Peripheral (Molex) power cable length: 150 mm | CPU power connector (4+4 pin): Yes | Efficiency: 90% | Power Factor Correction (PFC) type: Active | Depth: 140 mm | SATA power cable length: 150 mm | SATA power cable length: 600 | Max output current (-12V): 0.3 A | Bearing technology: HYB | CPU power cable length: 60 cm | Purpose: PC | Height: 86 mm | Max output current (+5V): 25 A | Combined power (+5Vsb): 15 W | On/off switch: Yes | PCI Express connector: Yes | Power protection features: Under voltage | Power protection features: Over current | Warranty period: 10 year(s) | 80 PLUS certification: 80 PLUS Gold | Combined power (+5V): 125 W | Max output current (+3.3V): 25 A | Combined power (+12V): 1000 W | Power protection features: Over power | Fan diameter: 12 cm | Power protection features: Short circuit | Power protection features: Over voltage | Mean time between failures (MTBF): 100000 h | Power protection features: Overheating | Number of fans: 1 fan(s) | Power factor: 0.9