



TP-Link Tapo C660 KIT - solar- powered outdoor IP surveillance camera



Modelis: Tapo C660KIT

Gamintojas: TP-LINK

EAN: 8885020624199

Prekės kodas: 579865

171.99€

Certification: CB, CE, FCC, DOE, CEC, RCM, KC, JFR,VCCI,NCC, BSMI, NTRA, IP65 | Maximum resolution: 3840 x 2160 pixels | Reset button: Yes | AC input voltage: 100 - 240 V | Operating temperature (T-T): -20 - 45 °C | Package type: Box | LED indicators: System | AC input frequency: 50/60 Hz | Product colour: White | Connectivity technology: Wired & Wireless | Package weight: 1.5 kg | Security algorithms: SSL/TLS | Security algorithms: WPA2-PSK | Built-in microphone: Yes | Type: IP security camera | Power source type: AC | Security algorithms: WPA | Security algorithms: 128-bit AES | Card reader integrated: Yes | Lens viewing angle, horizontal: 88° | Ethernet LAN: Yes | Package height: 116 mm | Package width: 218 mm | Package depth: 323 mm | Storage temperature (T-T): -20 - 60 °C | Lens viewing angle, diagonal: 105° | Compliance certificates: CE | Compliance certificates: RCM | Compliance certificates: VCCI | Compliance certificates: NCC | Virtual assistant: Amazon Alexa & Google Assistant | Operating relative humidity (H-H): 10 - 90% | Form factor: Bullet | Compatible

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

memory cards: MicroSD (TransFlash) | Compliance certificates: CB | Night vision: Yes | Compliance certificates: Federal Communications Commission (FCC) | Placement supported: Outdoor | Wi-Fi: Yes | Mounting type: Ceiling/wall | Depth: 147 mm | Remote viewing: Yes | Night vision distance: 12 m | Live view: Yes | Total megapixels: 8 MP | Video compression formats: H.264 | Sensor type: CMOS | Maximum aperture number: 1.6 | Built-in speaker(s): Yes | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Infra-red wavelength: 850 nm | Built-in siren: Yes | Compliance certificates: BSMI | Compliance certificates: KC | Height: 75 mm | Mobile operating systems supported: iOS 9.0 | Mobile operating systems supported: iOS 9.0 | Mobile operating systems supported: iOS 9.0 | Mobile operating systems supported: iOS 9.0 | Mobile operating systems supported: iOS 14 | Mobile operating systems supported: Android 6.0 | Mobile operating systems supported: iOS 11.0 | Mobile operating systems supported: iOS 11.0 | Alert notification type: Text alert message | Lens viewing angle, vertical: 45° | Mobile operating systems supported: Android 5.0 | Mobile operating systems supported: Android 5.0 | Infrared (IR) cut-off filter: Yes | Wi-Fi standards: 802.11g | LED type: IR | Wi-Fi standards: 802.11a | International Protection (IP) code: IP65 | Number of lenses: 1 | Mobile operating systems supported: iOS 10.0 | Mobile operating systems supported: Android 8.0 | Mobile operating systems supported: iOS 13 | Mobile operating systems supported: Android 9.0 | Wi-Fi standards: 802.11b | Built-in HDD: No | Width: 185 mm | Wi-Fi standards: Wi-Fi 4 (802.11n) | Mobile operating systems supported: iOS 15 | Number of cameras: 1 | Mobile operating systems supported: Android 4.0 | Mobile operating systems supported: Android 7.0 | Mobile operating systems supported: Android 7.0 | Frame rate: 20 fps | Digital zoom: 18x | Mobile operating systems supported: iOS 12 | Fixed focal length: 4 mm | Video streaming: Yes | Video motion detection: Yes | Storage relative humidity (H-H): 0 - 90%