



CABLE USB3.2 TYPE A TO C 25M/43396 LINDY



Modelis: 43396

Gamintojas: LINDY

EAN: 4002888433969

Prekės kodas: 580255

270.99€

The Lindy USB 3.2 Gen 1 Type A to C Hybrid Cable allows to deploy a USB Type C device up to 25m away from the computer whilst retaining SuperSpeed transfer rates of up to 5Gbps . It is typically used in meeting rooms and with video conference systems or webcams, which have their own power supply i.e. the Logitech Rally Camera.

This cable is designed for installation in walls, cable trays and through conduits. Aramid fibers ensure a robust cable structure and provide unparalleled strength and durability. The cable is CPR-certified, which means that the cable meets stringent fire safety regulations. Designed with low Radio Frequency Interference (RFI) and Electromagnetic Interference (EMI), this cable is suitable for sensitive environments where signal integrity is paramount.

Please note that this cable only works with self-powered devices and USB hubs with external power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

supplies.

- 10m Active Optical USB 3.2 Gen 1 Cable, backwards compatible with USB 2.0
- Supports transfer rates up to 5Gbps, backwards compatible with USB 2.0 devices
- Aramid fibers for a robust cable structure
- Low RFI/EMI for sensitive environments

Summary: Lindy 25m USB 3.2 Gen 1 Type A to C Fibre Optic Hybrid Cable. Cable length: 25 m.
Connector 1: USB A, Connector 2: USB C, USB version: USB 3.2 Gen 1 (3.1 Gen 1), Maximum data transfer rate: 5 Gbit/s, Connector contacts plating: Nickel, Product colour: Black, Magnetically shielded | Vendor Homepage: <https://www.lindy.co.uk/audio-video-c2/switches-c175/4x1-4k60-hdmi-seamless-multiview-switch-p14921> | Bend radius (min): 12.5 | Cable length: 25 | Connector 1 dimensions (WxDxH): 47.5 x 8.2 x 18.5 | Connector 2 dimensions (WxDxH): 45 x 8.2 x 14.5 | Weight: 1000 | Cable jacket material: Thermoplastic elastomer (TPE) | Cable type: Round cable | Connector 1: USB A | Connector 1 form factor: Straight | Connector 1 gender: Male | Connector 2: USB C | Connector 2 form factor: Straight | Connector 2 gender: Male | Connector contacts plating: Nickel | Magnetically shielded: Yes | Maximum data transfer rate: 5 | Plug and Play: Yes | Power consumption: 1.5 | Product colour: Black | USB version: USB 3.2 Gen 1 (3.1 Gen 1) | Package depth: 240 | Package height: 65 | Package weight: 1180 | Package width: 240 | Manual: Yes | Quantity per pack: 1 | Operating temperature (T-T): -20 - 70 | Storage temperature (T-T): -30 - 75 | Certification: CE, UKCA, FCC, RoHS, REACH & California Proposition 65 | Warranty period: 2 | Packaging content: 25m USB 3.2 Gen 1 Type A to C Hybrid Cable Lindy manual | Model: 43396 | Model name: 25m USB 3.2 Gen 1 Type A to C Fibre Optic Hybrid Cable | Units per Pallet: 0 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.003981 | Unit Calculated Weight: 1.16