

Sharp P506 Digital signage flat panel 127 cm (50") 700 cd/m² Black 24/7

Gamintojas: **SHARP** · Modelis: **PNP506** · EAN: **4550556131117** · Prekės kodas: **580643**



2 100,90 €

Kaina su PVM

Be PVM: **1 736,28 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Enhanced imaging precision – when brand consistency and corporate identity are important, Sharp's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- ✓ Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- ✓ Security assured – 802.2x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- ✓ Mission-critical performance – with 700 cd/m² brightness, long-life components and robust flame-resistant metal chassis, the P6 series is engineered to deliver lasting clarity and durability in challenging environments without the need for bulky housings.
- ✓ Trusted integration – full compatibility with major AV ecosystems, including Crestron XiO Cloud and NVX, Q-Sys, Cisco Webex, Matrox IPMX, and CMS solutions, ensures seamless setup and scalability.



Aprašymas

When reliability, security, and exceptional visual performance are mandatory, the Sharp MultiSync® P6 Series delivers with precision and resilience. Engineered for mission-critical applications and high-end signage, the P6 Series combines robust durability with advanced visual technologies to meet the most demanding commercial needs. With 700 cd/m² brightness, a high-haze panel, and SpectraView™ Engine, it delivers outstanding image clarity and colour accuracy even in challenging lighting conditions. Despite its slim profile, the P6 Series is endorsed for use in heavy traffic

spaces with a durable all-metal chassis that complies to the strictest fire safety standards. Building on NEC's trusted heritage, the next generation Sharp P6 Series is designed for longevity and integration flexibility. Its modular architecture supports custom computing options by Intel® SDM or Raspberry Pi, and flexible connectivity including AVoverIP for versatile deployments. Native video daisy chaining via HDMI and DisplayPort enables content to be easily cloned or expanded across multiple displays. Compatibility with leading platforms such as Crestron, Cisco Webex, and Q-Sys enhances its future-proof appeal, while 802.1x LAN support safeguards robust security against cyber threats. Purpose-designed for control rooms, passenger information, and prestige retail or corporate signage, the P6 Series delivers uncompromising performance, day after day.

Techninė specifikacija

Specifications	
Sandėlio grupė	Displays > Lcd Large Format [+101][-116]
Display	
Display diagonal	127 cm (50")
Display resolution	3840 x 2160 pixels
Display brightness	700 cd/m²
Panel type	VA
LED backlight	Yes
LED backlighting type	Direct-LED
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	8000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.073 billion colours
Pixel pitch	0.285 x 0.285 mm
Active display area (W x H)	1095 x 616 mm
Display diagonal (metric)	126 cm
Horizontal scan range	15 - 135 kHz
Vertical scan range	23 - 76 Hz
Haze rate	25%
Ports & interfaces	
USB port	Yes
Consumer Electronics Control (CEC)	Yes
DisplayPorts out	1
RS-232C	Yes
Audio Return Channel (ARC)	Yes
Audio	

Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	10 W
Design	
Product design	Digital signage flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Panel mounting interface	300 x 300 mm
Bezel width (bottom)	1.4 cm
Bezel width (side)	1.1 cm
Bezel width (top)	1.1 cm
Performance	
Purpose	Universal
Operating hours (hours/days)	24/7
Power	
Power consumption (typical)	95 W
Power consumption (standby)	2 W
Energy efficiency class (SDR)	G
Energy consumption (SDR) per 1000 hours	85 kWh
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Weight & dimensions	
Display width	1122 mm
Display depth	67 mm
Display height	645 mm
Display weight	18 kg
Packaging data	
Package width	1245 mm
Package depth	188 mm
Package height	785 mm
Package weight	23 kg
Packaging content	
Remote control included	Yes

Cables included	HDMI, Power
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	10 - 80%
Sensors	
Temperature sensor	Yes
Eco sensor	Yes
Network	
Ethernet LAN	Yes
Ethernet LAN data rates	100 Mbit/s
Features	
Wall mountable	Yes
Technical details	
Compliance certificates	Electromagnetic Compatibility (EMC), UKCA, RoHS, UL, cUL, CSA, Federal Communications Commission (FCC), CE, REACH
Matmenys ir svoris	
Matmenys (I × P × A)	124,00cm × 77,00cm × 19,00cm
Svoris	23,00kg