

Switch UBIQUITI USW-PRO-48-POE Type L3 Rack 48x10Base-T 100Base-TX 1000Base-T 4xSFP PoE+ ports 48 600 Watts USW-PRO-48-POE

Gamintojas: **UBIQUITI** · Modelis: **USW-PRO-48-POE** · EAN: **817882027656** · Prekės kodas: **580852**



1 274,90 €

Kaina su PVM

Be PVM: **1 053,64 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Second-Generation UniFi Switching

We've redesigned our UniFi Switches from the ground up.

Near Silent Cooling

Our new airflow design reduces the need for fan usage.

Powerful Hardware and Software

UniFi Switches offer a variety of features, including 10G SFP+ ports, PoE+ or PoE++ support, and Layer 3* switching capabilities.

Redundant Power System

UniFi SmartPower RPS, USP-RPS, is our PSU failover system.

Power Supply Failure

In the event of a UniFi switch power supply failure, the USP-RPS automatically supplies redundant power to the failed device.

UniFi SmartPower

One UniFi SmartPower device can support up to 6 devices until the failed device is replaced.

Touchscreen Display

The 1.3" touchscreen display allows easy monitoring and quick troubleshooting.

Summary: Ubiquiti UniFi Pro 48-Port PoE. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 48. Full duplex. Switching capacity: 176 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at. DC input voltage: 44 - 57 V. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: <https://switch.ui.com/gen2/> | Switch type: Managed | Switch layer: L2/L3 | Basic switching RJ-45 Ethernet ports quantity: 48 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP+ module slots quantity: 4 | Networking standards: IEEE 802.3af/IEEE 802.3at | 10G support: Yes | Port mirroring: Yes | Full duplex: Yes | Auto MDI/MDI-X: Yes | Auto-sensing: Yes | Flow control support: Yes | Spanning tree protocol: Yes | VLAN support: Yes | Switching capacity: 176 | Throughput: 88000 | Forwarding rate: 130.944 | Static route: Yes | Jumbo frames support: Yes | DHCP features: DHCP server | Authentication type: IEEE 802.1x,RADIUS | Rack mounting: Yes | Form factor: 1U | Product colour: Silver | LED indicators: Activity/Link/PoE/Speed/System | Power supply included: Yes | Number of power supply units: 1 | AC input voltage: 100 - 240 | AC input frequency: 50 - 60 | DC input voltage: 44 - 57 | Input current: 11.54 | Power over Ethernet (PoE): Yes | Power over Ethernet plus (PoE+) ports quantity: 40 | Power over Ethernet (PoE) power per port: 64 | Total Power over Ethernet (PoE) budget: 600 | Operating temperature (T-T): -5 - 40 | Operating relative humidity (H-H): 10 - 90 | Width: 442.4 | Depth: 399.6 | Height: 43.7 | Weight: 6250 | Certification: CE, FCC, IC | Harmonized System (HS) code: 85176990 | Unit Calculated Weight: 7.35 | Product Net Weight: 6.25 | Unit Calculated Volume: 0.03617 | Units per Shipping Box: 2 | Unit Width: 12 | Units per Pallet: 0 | Shipping Box Height: 53.5 | Unit Depth: 52 | Unit Height: 51 | Name: NET SWITCH 48PORT 1000M 2SFP/POE USW-PRO-48-POE UBIQUITI | Model name: USW-PRO-48-POE

Techninė specifikacija

Matmenys ir svoris

Matmenys (I × P × A)

52,00cm × 12,00cm × 51,00cm