



Ubiquiti Pro Max 24 L3 2.5G Ethernet (100/1000/2500) 1U Grey



Modelis: USW-Pro-Max-24

Gamintojas: UBIQUITI

EAN: 810084692738

Prekės kodas: 580963

480.99€

Compliance certificates: CE | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid. | Warnings: Follow the safety guidelines for electrical current. | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: Industry Canada (IC) | Stackable: Yes | Loop protection: Yes | SFP+ module slots quantity: 2 | Virtual LAN features: Voice VLAN | Sustainability certificates: Federal Communications Commission (FCC) | Throughput: 56 Gbit/s | Switch layer: L3 | Port mirroring: Yes | Flow control support: Yes | Rate limiting: Yes | Sustainability certificates: CE | Rack mount kit: Yes | 2.5G Ethernet (copper) ports quantity: 8 | Static route: Yes | Broadcast storm control: Yes | Gigabit Ethernet (copper) ports quantity: 16 | Rack mounting: Yes | Width: 442.4 mm | Power source: AC/DC | Basic switching RJ-45 Ethernet ports quantity: 24 | IGMP snooping: Yes | Networking standards: IEEE 802.1x | VLAN support: Yes | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | Power over Ethernet

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(PoE): No | Reset button: Yes | Switching capacity: 112 Gbit/s | Form factor: 1U | Weight: 4.3 kg | Operating temperature (T-T): -5 - 40 °C | Depth: 325 mm | Power connector: AC/DC | Product colour: Grey | Height: 43.7 mm | Cables included: Power | DHCP features: DHCP snooping | Operating relative humidity (H-H): 10 - 90% | Power supply included: Yes | 10G support: Yes | Display type: LCM | DHCP features: DHCP relay | Power consumption (max): 50 W | AC input frequency: 50/60 Hz | LED indicators: Speed | Jumbo frames support: Yes | LED indicators: Network | AC input voltage: 100 - 240 V | LED indicators: Link | LED indicators: Status