

Ubiquiti Dream Machine Pro Max gateway/controller 10, 100, 1000, 2500 Mbit/s

Gamintojas: **UBIQUITI** · Modelis: **UDM-Pro-Max** · EAN: **810084693254** · Prekės kodas: **580971**



693,90 €

Kaina su PVM

Be PVM: **573,47 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

SFP+ ports quantity: 2 | Warnings: Do not use in damp conditions. | Warnings: Do not open the appliance - risk of electric shock. | Electrostatic Discharge (ESD) protection (air): 15 kV | Electromagnetic (EMP) protection (contact): 8 kV | Warnings: Make sure the unit is stably mounted and ventilated. | Enclosure material: Aluminium/SGCC | Electromagnetic (EMP) protection: Yes | Electrostatic Discharge (ESD) protection (contact): 8 kV | Port aggregation: Yes | Compliance certificates: National Defense Authorization Act (NDAA) | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: CE | Compliance certificates: Industry Canada (IC) | Electromagnetic (EMP) protection (air): 15 kV | Quality of Service (QoS) support: Yes | Weight: 4.7 kg | Power consumption (max): 60 W | Multicast support: Yes | Internal memory: 8000 MB | Depth: 285.6 mm | Product colour: Grey | Mounting type: Rack mounting | VLAN support: Yes | Processor frequency: 2000 MHz | Input frequency: 50/60 Hz | DHCP server: Yes | LED indicators: Link | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 1000 Mbit/s | LED indicators: Ready | Firewall security: Yes | Built-in processor: Yes | LED indicators: Error | Input current: 2 A | Flash memory: 32000 MB | DC input voltage: 12 V | Operating relative humidity (H-H): 5 - 95% | Operating temperature (T-T): -10 - 40 °C | Processor manufacturer: ARM | Heat dissipation: 205 BTU/h | Processor family: ARM Cortex | SSD capacity: 128 GB | LED indicators: Activity | Display type: LCM | Processor model: Cortex-A57 | Reset button: Yes | Ethernet

LAN data rates: 10 | Control display unit: Yes | Ethernet LAN (RJ-45) ports: 9 | WAN connection: Ethernet (RJ-45), SFP+ | Routing protocols: OSPF | Routing protocols: BGP | Height: 43.7 mm | Cables included: AC | Width: 442.4 mm | Power over Ethernet (PoE): No | Ethernet LAN data rates: 2500 Mbit/s | Rack capacity: 1U | Number of processors installed: 1 | Input voltage: 100 - 240 V

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	52,00cm × 12,00cm × 42,00cm
Svoris	5,94kg