



TP-Link Omada 52-Port Gigabit L2+ Managed Switch with 48- Port PoE+



Modelis: TL-SG3452P

Gamintojas: TP-LINK

EAN: 1210002611947

Prekės kodas: 581305

639.99€

Power source: AC | AC input voltage: 100 - 240 V | Manual: Yes | Operating relative humidity (H-H): 10 - 90% | Form factor: 1U | Reset button: Yes | Cables included: AC | Power over Ethernet (PoE): Yes | Basic switching RJ-45 Ethernet ports quantity: 48 | SFP module slots quantity: 4 | Total Power over Ethernet (PoE) budget: 384 W | Networking standards: IEEE 802.3x | Width: 440 mm | Web-based management: Yes | Depth: 330 mm | Operating temperature (T-T): 0 - 40 °C | Networking standards: IEEE 802.1w | Power consumption (max): 464.2 W | Switching capacity: 104 Gbit/s | Number of fans: 3 fan(s) | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Power over Ethernet (PoE) power per port: 30 W | LED indicators: Yes | Networking standards: IEEE 802.1p | Height: 44 mm | Quick start guide: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | Product colour: Black | AC input frequency: 50/60 Hz | Password protection: Yes | VLAN support: Yes | Storage relative humidity (H-H): 5 - 90% | Power supply included: Yes | Networking standards: IEEE 802.1D | Rack mounting: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Jumbo frames support: Yes | Package type: Box | Number of static routes: 48 | DHCP features: DHCP snooping | DHCP features: DHCPv6 client | DHCP features: DHCP server | DHCP features: DHCP client | DHCP features: DHCP relay | SSH/SSL support: Yes | DHCP features: DHCPv6 snooping | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Console port: RJ-45/micro-USB | Cloud-managed: Yes | ARP inspection: Yes | MAC address table: 16000 entries | Flow control support: Yes | Broadcast storm control: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | Multicast support: Yes | Power over Ethernet plus (PoE+) ports quantity: 48 | Store-and-forward: Yes | Virtual LAN features: Tagged VLAN | Port mirroring: Yes | 10G support: No | Virtual LAN features: Voice VLAN | BPDU filtering/protection: Yes | Number of VLANs: 4000 | Static route: Yes | Link aggregation: Yes | Policy-based routing: Yes | Virtual LAN features: Private VLAN | Switch layer: L2/L3 | Virtual LAN features: Protocol-based VLAN | Forwarding rate: 77.38 Mpps | Head-of-line (HOL) blocking: Yes | Packet buffer memory: 12 MB | Virtual LAN features: MAC address-based VLAN | Power connector: AC-in jack | IGMP snooping: Yes | System event log: Yes | Authentication: MAC-based authentication, Port-based authentication | GARP VLAN Registration Protocol (GVRP): Yes | MIB support: Yes | Access Control List (ACL): Yes | Management protocols: SNMPv1/v2c/v3, SNTP | Rate limiting: Yes | Loop protection: Yes | Switch type: Managed | Active link detection: Yes | Heat dissipation: 1584.08 BTU/h | IP routing: Yes