

PA348CGV makes it easy to achieve the exact look you desire quickly, easily and precisely.

Ultra-wide QHD display for incredibly detailed images

The ultra-wide QHD panel on ProArt Display PA348CGV features 2.4x the resolution of a Full HD display, so it provides 35% more onscreen space than other Full HD monitors of a similar size, making multitasking more enjoyable and efficient. Compatible with HDR-10 format and VESA DisplayHDR 400 for brighter whites and darker blacks, resulting in a rich and lifelike viewing experience that helps you fully realize your creative vision.

Bring out the true beauty of your pictures

The ProArt display delivers industry-standard 98% DCI-P3 and 100% sRGB/Rec. 709 color gamut for rich, vivid reproduction that ensures every detail of your photos is clear and lifelike.

2D/3D Rendering friendly

Up to a 120 Hz variable refresh rate (VRR) with FreeSync Premium Pro, allowing creators to create fast-rendering games and conduct quality checks on one display. High frame rate brings smooth visuals delivers comfortable viewing experience.

*FreeSync Premium Pro up to 120 Hz for DisplayPort and USB-C ports, Adaptive-Sync up to 100Hz for HDMI port.

True color, right out of box

Color professionals rely on color-accurate displays to ensure that their creations look exactly as intended. ProArt Display PA348CGV is factory calibrated and Calman Verified to guarantee industry-leading color accuracy $\Delta E < 2$. Every ProArt display undergoes stringent, meticulous testing to ensure smoother color gradation. Consumer of pro, you're assured color-accurate viewing and content-creation experiences.

Quick color-gamut adjustment

ASUS-exclusive ProArt Preset provides multiple modes for quick color-gamut adjustment. Whether you're color grading, video editing or manipulating photos, you can switch and match your needs easily.

Focus on what matters

Desk C-clamp

A convenient mounting bracket is included to help free up desk space. The bracket can clamp to the edge of almost any flat work surface, and the mounting arm of PA348CGV slips right into it.

*Desk C-clamp availability may vary by region.

*the photo for demo only

The USB-C that does it all

ProArt Display PA348CGV gives you unparalleled compatibility with USB-C, HDMI and DisplayPort most multimedia devices. The integrated USB-C port supports data transfers, DisplayPort and also support 90W power delivery. PA348CGV also serves as a USB hub, meaning that when you connect to it via USB-C (using C to C cable, or C to A cable), your device gains access to whatever peripherals are connected to the USB ports.

Accurate real-time on-set preview

QuickFit Plus is clever feature overlays a grid on the screen that allows to align and preview. Center marker and safety area it can real-time preview when you are on-set shooting to avoid video image beyond the screen. Ruler provides actual size of inch ruler in the edge; you also can customize the working size to fit your preference.

Protect your eyes with ASUS Eye Care technology

ASUS Ultra-Low Blue Light technology

Exclusive ASUS Ultra-Low Blue Light technology protects you from blue-light emissions that may be harmful to your vision. It offers four blue-light filter settings that are easily accessed through the on-screen menu via the hotkey.

ASUS Flicker-Free technology

ASUS Flicker-Free technology provides a more comfortable viewing experience and work environment by reducing on-screen flicker to minimize eye strain, headaches and eye fatigue when you spend long hours in front of the display.

Versatile comfort with ergonomic stand design

A comfortable viewing position is always within reach thanks to ergonomically-designed stand with tilt, swivel and height adjustments provides a superb range of viewing options for increased productivity and comfort. Cable management design helps you organize and hide various cables to keep your desk area tidy. Furthermore, the quick-release stand makes it easy to attach the display via the integrated VESA wall mount – screw-free, so it's done in seconds!

Techninė specifikacija

Ekranas	
Ekranas įstrižainė	86,4 cm (34")
Ekranas rezoliucija	3440 x 1440 pikseliai
Natūralus kraštinių santykis	21:9
Lietimui jautrus ekranas	Ne
HD tipas	UltraWide Quad HD
Skydo tipas	IPS
Reakcijos laikas	2 ms
Ekranas forma	Plokščias
Kontrasto santykis (tipinis)	1000:1
Maksimalus atnaujinimo dažnis	120 Hz
Ekranas spalvų skaičius	1,073 milijardo spalvų
Foninio apšvietimo tipas	LED
Ekranas ryškumas (pikinis)	400 cd/m ²
Ekranas ryškumas (tipinis)	350 cd/m ²
Ekranas paviršius	Matinis
Matymo kampas, horizontalus	178°
Matymo kampas, vertikalus	178°
Pikselių žingsnis	0,2325 x 0,2325 mm
Pikselių tankumas	110 ppi
Horizontali diapazono riba	185 - 185 kHz
Vertikali diapazono riba	48 - 120 Hz
Matomas dydis, horizontalus	80 cm

Matomas dydis, vertikalus	33,5 cm
Horizontalus skaitmeninis dažnis	30 - 151 kHz
Vertikalus skaitmeninis dažnis	30 - 100 Hz
Palaikoma HDR	Taip
Didelio dinaminio diapazono (HDR) technologija	High Dynamic Range 10 (HDR10)
Spalvų gamos standartas	DCI-P3
Spalvų gama	98%
Palaikomas sRGB (įprastas)	100%
Veikimo charakteristikos	
NVIDIA G-SYNC	Ne
„AMD FreeSync“	Taip
„AMD FreeSync“ tipo	„FreeSync Premium Pro“
Apsaugos nuo mirgėjimo technologija	Taip
Mažo kiekio mėlynos šviesos technologija	Taip
Multimedija	
Įmontuoti garsiakalbiai	Taip
Integruota kamera	Ne
Garsiakalbių skaičius	2
RMS galingumas	4 W
Konstrukcija	
Pozicija rinkoje	Grafinis dizainas
Produkto spalva	Juoda
Kojelių spalva	Juoda
Ryšys	
Įmontuotas USB jungčių daugiklis	Taip
HDMI	Taip
Ausinių išvestis	Taip
USB koncentratoriaus versija	3.2 Gen 1 (3.1 Gen 1)
USB aukštakrypčio prievado tipas	C tipo USB
Priešsrovinių prievadų skaičius	1
C tipo USB kylančiųjų prievadų skaičius	1
USB A tipo žemakrypčių prievadų skaičius	4
„USB Power Delivery“	Taip
USB maitinimo tiekimas iki	90 W

HDMI portų kiekis	2
HDMI versija	2.0
„DisplayPort“ kiekis	1
„DisplayPort“ versija	1.4
Ausinių išvestys	1
Ausinių jungtis	3,5 mm
HDCP	Taip
HDCP versija	2.2

Ergonomija

VESA tvirtinimo pagrindas	Taip
Kabelio spynos lizdas	Taip
Aukščio reguliavimas	Taip
Suderinama su VESA sienos tvirtinimo sistema	100 x 100 mm
Laido spynos lizdo tipas	Kensington
Reguliuojamas aukštis (maks.)	11,5 cm
Sukiojamas	Taip
Pasukamas	30 - -30°
Pokrypio reguliavimas	Taip
Posvyrio kampo intervalas	23 - -5°

Energijos valdymas

Energijos vartojimo efektyvumo klasė (SDR)	G
Energijos suvartojimas	29,7 W
Energijos suvartojimas (PowerSave)	0,5 W
AC įėjimo įtampa	100 - 240 V
AC įėjimo dažnis	50 - 60 Hz
Energijos vartojimo efektyvumo klasė (HDR)	G
Energijos suvartojimas (laukimo režimu)	0,5 W
Energijos suvartojimas (off)	0,3 W
Maitinimo tipas	Vidinis

Svoris ir matmenys

Plotis (su stovu)	817,6 mm
Gylis (su stovu)	245 mm
Aukštis (su stovu)	568,9 mm
Svoris (su stovu)	12,2 kg
Plotis (be stovo)	817,6 mm

Gylis (be stovo)	68,9 mm
Aukštis (be stovo)	368,2 mm
Svoris (be stovo)	7,8 kg

Pakuotės duomenys

Pakuotės plotis	930 mm
Pakuotės gylis	300 mm
Pakuotės aukštis	488 mm
Paketo svoris	17 kg
Pakuotės tipas	„Box“

Pakuotės turinys

Pridėti kabeliai	DisplayPort, HDMI, C tipo USB
------------------	-------------------------------


Techninė informacija

Būdingas atnaujinimo dažnis	60 Hz
-----------------------------	-------

Matmenys ir svoris


Matmenys (I × P × A)	49,00cm × 30,00cm × 93,00cm
Svoris	17,00kg

Energijos efektyvumas ir ekologinis projektavimas



Energijos efektyvumo klasė **G** A-G

- › [Energijos etiketė](#)
- › [Gaminio informacijos lapas](#)
- › [EPREL duomenų bazė](#)



Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

ASUSTeK Computer Inc

Li-Te Road 15, 112 Taipei, TW

asus.com

ATSAKINGAS ASMUO ES

ASUS France S.A.R.L.

Allee bienvenue 10, 93160 Paris, FR

channel.asus.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt