



X-SENSE FS121 Smoke Detector Kit



Modelis: FS121

Gamintojas: X-SENSE

EAN: 810194780028

Prekės kodas: 581549

261.99€

X-SENSE FS121 Smoke Detector Kit

Ensure comprehensive protection for your entire home or office with the X-SENSE FS121 kit, which consists of 12 XS01-M smart smoke detectors and an SBS50 base station. The system uses photoelectric smoke sensors and enables wireless communication between them, so that triggering one alarm activates all connected devices. An additional advantage is its integration with the X-Sense Home Security app, which offers, among other things, useful notifications and a device testing option.

Smart protection for your entire home

The XS01-M sensors can function as classic wireless alarms or work with the SBS50 base station to offer more advanced monitoring features. Upon detecting smoke, all connected alarms trigger an alert simultaneously, which increases the safety of household members and allows for a faster response to the threat. The system supports up to 24 connected Link+ alarms and up to 50 devices

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

connected to a single base station.

Constant access to notifications and control via the app

Once connected to the SBS50 base station and the X-Sense Home Security app, users can monitor the status of devices from anywhere. The system sends real-time notifications about alarms, low battery levels, and more. It is also possible to test and silence devices, as well as share them with other household members.

Reliable wireless communication

The kit operates on the 868 MHz frequency, ensuring stable communication between devices even over long distances. The sensors offer a transmission range of up to 500 m in open space, while the base station supports a 2.4 GHz Wi-Fi connection with a range of up to 50 m from the router. This allows the system to effectively secure multiple rooms and floors without the need for additional wiring.

Loud alarm and mute function

Each sensor emits an alarm with a volume of approximately 85 dB (from a distance of 3 meters), effectively warning of a fire hazard. The system is also equipped with an alarm mute function for approximately 9 minutes, which is useful, for example, when the alarm is triggered accidentally, such as while cooking. The base station, on the other hand, has a built-in speaker with voice messages at a volume of up to 110 dB and allows you to select an alarm melody.

Long-lasting performance and easy installation

The XS01-M sensors use replaceable CR123A lithium batteries and offer a service life of up to 10 years. Installation is simple and can be performed on the ceiling or wall using the included mounting hardware. Additionally, the sensors' compact dimensions of 78 × 78 × 48 mm allow them to be discreetly placed in various rooms without affecting the interior's aesthetics.

Included

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Base station
- Sensor x12
- Power supply
- Power cable
- Mounting bracket
- Screws
- Anchors
- CR123A battery (pre-installed)
- User manual

Smoke sensor

Manufacturer	X-SENSE
Model	XS01-M
Safety standards	EN 14604:2005+AC:2008
Sensor type	Photoelectric
Lifespan	Up to 10 years
Power supply	Replaceable 3 V CR123A lithium battery
Battery life	Approx. 5 years (weekly test, wireless network) Approx. 3-5 years (when connected to a base station)
Alarm volume	≥ 85 dB at a distance of 3 m at 3.2 ± 0.3 kHz (pulsed alarm)
Operating temperature	4°C to 38°C
Operating humidity	≤ 85% RH (non-condensing)
Silencing time	Approx. 9 min
LED indicator	LED (red/yellow/green)
Operating frequency	868 MHz
Maximum number of connected devices	Up to 24 wireless units (compatible only with X-Sense Link+ wireless alarms)
Connection range	Up to 500 m (in open space)
Weight	95 g

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Dimensions	78 × 78 × 48 mm
-------------------	-----------------

Base station

Manufacturer	X-SENSE
---------------------	---------

Model	SBS50
--------------	-------

Power supply	Input: 100–240 V AC 50/60 Hz Output: 5.0 V = 1.0 A
---------------------	---

Alarm volume	100 dB
---------------------	--------

Operating temperature	4°C to 38°C
------------------------------	-------------

Operating humidity	0–85% RH (non-condensing)
---------------------------	---------------------------

LED indicator	LED (red/yellow/green)
----------------------	------------------------

Operating frequency	868 MHz
----------------------------	---------

Wi-Fi frequency	2.4 GHz (not compatible with 5 GHz)
------------------------	-------------------------------------

Wi-Fi range	Up to 50 m
--------------------	------------

Wireless network standard	IEEE 802.11 b/g/n
----------------------------------	-------------------

Maximum number of supported devices	Up to 50 devices
--	------------------

Weight	78 g
---------------	------

Dimensions	90 × 90 × 26.5 mm
-------------------	-------------------

App	X-Sense Home Security
------------	-----------------------

GPSR Link: https://psr-assets.innpro.pl/smarthome/sg_smarthome_actuators.pdf, Gross weight: 1720, Net weight: 1218, Box length: 25,00, Box width: 14,50, Box height: 18,00, Information about data generation: <https://dataact.innpro.pl/X-Sense/0810194780028>, GARAN: <https://garan.innpro.pl/x-sense/0810194780028>