



be quiet!
POWER ZONE 2
850W power
supply unit
20+4 pin ATX
ATX Black

Modelis: BP007EU

Gamintojas: BE QUIET!

EAN: 4260052191378

Prekės kodas: 581811

160.99€

Product colour: Black | Package width: 248 mm | Operating temperature (T-T): 0 - 40 °C | Power protection features: Short circuit | Power protection features: Over voltage | Cooling type: Active | On/off switch: Yes | AC input frequency: 50/60 Hz | 80 PLUS certification: 80 PLUS Platinum | Cabling type: Fully-Modular | Shipping (inner) case width: 28.2 cm | Shipping (inner) case length: 65.1 cm | Storage temperature (T-T): -40 - 70 °C | Power protection features: Under voltage | Power protection features: Over current | Total power: 850 W | Noise level: 24.9 dB | Power protection features: Surge & inrush | Screws included: Yes | Shipping (inner) case gross weight: 19.3 kg | Package height: 102 mm | Operating relative humidity (H-H): 0 - 85% | Manual: Yes | AC input voltage: 100 - 240 V | Mean time between failures (MTBF): 100000 h | Power protection features: Over power | Width: 150 mm | Storage relative humidity (H-H): 0 - 95% | Illumination: No | Package depth: 328 mm | Power protection features: Overheating | Products per shipping (inner) case: 6 pc(s) | Package type: Box |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Peripheral (Molex) power connectors (4-pin): 1 | Shipping (inner) case height: 34.6 cm | Package weight: 3.21 kg | Purpose: PC | Efficiency: 92.3% | Power factor: 0.98 | Height: 86 mm | EPS power connector (8-pin): Yes | Depth: 160 mm | Power supply unit (PSU) form factor: ATX | Number of +12V rail(s): 1 | Number of fans: 1 fan(s) | Fan diameter: 14 cm | Compliance certificates: CCC | Compliance certificates: RoHS | Compliance certificates: CE | PCI Express power cable length: 60 cm | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: UKCA | Sustainability certificates: ENERGY STAR | Sustainability certificates: ErP | Compliance certificates: WEEE | Compliance certificates: RCM | SATA power cable length: 700 | Compliance certificates: TÜV mark | Peripheral (Molex) power cable length: 1000 | Max output current (+5V): 20 A | SATA power cable length: 850 mm | Manual languages: German | Manual languages: Russian | CPU power connector (4+4 pin): Yes | Combined power (+5Vsb): 15 W | Combined power (+3.3V): 120 W | Max output current (+12V): 70.8 A | Manual languages: Polish | Manual languages: Ukrainian | Max output current (+3.3V): 20 A | Combined power (+5V): 120 W | Compliance certificates: BSMI | SATA power cable length: 1000 mm | ATX version: 3.1 | Compliance certificates: CB | Motherboard power connector: 20+4 pin ATX | Waste Electrical and Electronic Equipment (WEEE) compliance: Yes | PCI Express power connectors (6+2 pin): 3 | Peak power: 920 W | Number of SATA power connectors: 7 | EPS version: 2.92 | Manual languages: Spanish | Hold time: 21.1 ms | PCI Express connector: Yes | Maximum input current (@110V): 10 A | Manual languages: French | Manual languages: English | Sustainability certificates: Triman | Maximum input current (@220V): 5 A | SATA power cable length: 550 | Max output current (-12V): 0.5 A | Max output current (+5Vsb): 3 A | Motherboard power cable length: 60 cm | Cable ties included: Yes | Combined power (-12V): 6 W | Combined power (+12V): 849.6 W | CPU power cable length: 70 cm | CPU P4 connector (4-pin): 1 | Bearing technology: Rifle | PCI Express power connectors (16-pin): 1