



Gigabyte P450B power supply unit 450 W 20+4 pin ATX ATX Black



Modelis: GP-P450B

Gamintojas: GIGABYTE

EAN: 4719331551612

Prekės kodas: 582186

41.99€

Max output current (+3.3V): 18 A | PCI Express connector: Yes | Floppy disk drive connector: Yes | Hold time: 16 ms | Floppy drive power connector: 1 | Product colour: Black | Power supply unit (PSU) form factor: ATX | PCI Express power cable length: 55 cm | AC input frequency: 50 - 60 Hz | Harmonized System (HS) code: 84733020 | CPU power cable length: 60 cm | Bearing technology: HDB | Depth: 140 mm | Width: 150 mm | Max output current (-12V): 0.3 A | AC input voltage: 100 - 240 V | Max output current (+5V): 15 A | Motherboard power connector: 20+4 pin ATX | Efficiency: 85% | Motherboard power cable length: 55 cm | Peripheral (Molex) power cable length: 500 mm | ATX power connector (20+4 pin): Yes | Fan diameter: 12 cm | Combined power (-12V): 3.6 W | On/off switch: Yes | Input current: 8 - 4 A | Combined power (+5V): 103 W | Combined power (+3.3V): 103 W | CPU power connector (4+4 pin): Yes | Fan location: Top | Combined power (+5Vsb): 15 W | 80 PLUS certification: 80 PLUS Bronze | Mean time between failures (MTBF): 100000 h | Number of fans: 1 fan(s) | Cabling type: Non-Modular | Power factor: 0.9 | Power protection features: Under voltage |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Power protection features: Over current | Power protection features: Short circuit | Power protection features: Over voltage | Purpose: PC | Power protection features: Overheating | SATA power cable length: 500 | ATX version: 2.31 | Total power: 450 W | Power protection features: Over power | Height: 86 mm | Max output current (+12V): 36 A | Power Factor Correction (PFC) type: Active | Cooling type: Active | Number of SATA power connectors: 6 | Peripheral (Molex) power connectors (4-pin): 3 | PCI Express power connectors (6+2 pin): 2 | Max output current (+5Vsb): 3 A | Combined power (+12V): 432 W