

AG Neovo SC-2702 computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD Black

Gamintojas: **AG NEOVO** · Modelis: **SC-2702** · EAN: **4710739597325** · Prekės kodas: **582199**



284,89 €

Kaina su PVM

Be PVM: **235,45 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Full HD 1920 x 1080 resolution
- ✓ Versatile connectivity: VGA, HDMI, Composite (BNC) inputs
- ✓ Composite (BNC) passive loop-through output port
- ✓ Quick Image settings: CCTV Mode, Gamma Selection, Black-level Adjustment, Contrast Enhancer
- ✓ Designed and developed for continuous 24/7 operation



Aprašymas

The SC-2702 27-inch surveillance monitor with BNC connector features 3-sided bezel-less specifically designed for security operators – especially those with a 24/7 operating multi-screen setup who are looking for efficient video monitoring. The SC-2702 provides value-added video enhancement controls that help create detailed images for low-light footage. Its optional monitor mounting solutions support single or multiple monitor setups. In terms of cost-to-performance, this model is the solution for productivity in modern operator workstations.

3-SIDED BEZEL LESS MONITOR INCREASE PRODUCTIVITY

The SC-2702 adopts a seamless 3-sided bezel-less design to create a productive work environment and reduce gaps between monitors. Perform rapid analysis, manage, and control video sources from all locations. Evolving situations require quick decisions, which seamless monitors can help with.

MULTIPLE MONITOR SETUPS MADE EASY

With VESA 100 x 100mm, the SC-2702 is compatible with AG Neovo's mounting portfolio of desk and wall mounts. Whether you're looking for a dual, quad, or more monitor set-up, AG Neovo is a one-stop-shop for creating ergonomic workstations in a control room.

HIGHER COST PERFORMANCE

Designed with long-hour monitoring in mind, you can expect a reduction in system maintenance efforts and consequentially higher cost performance. The SC-2702 is commercial grade and meant to work 24/7, 365 days a year. Static images that would otherwise cause screen burn-in are gone with AG Neovo's patented Anti-Burn-in technology. Expect prolonged life for LCD screens.

PERFECT MATCH TO CCTV IMAGES

There is a special pre-configured CCTV Mode that maximises image clarity in low-light footage. Quickly fine-tune your video footage with adjustments for sharpness, saturation, contrast, brightness, and more. Don't waste time testing and re-adjusting constantly, this product already has it all figured out!

ENHANCED GAMMA SELECTION

Offering an enhanced gamma selection makes for amazing visual optimization. Improve the light, shadow, and colour balance quality of your videos with ease.

MISSING DETAILS IN DARK SCENES IS A THING OF THE PAST

More detail from black-level adjustment means improved visibility of dark images.

CONTRAST ENHANCER

By coming with a contrast enhancer, the surveillance monitor enables low-contrast images to become more clear and defined.

ADAPTABLE TO SURVEILLANCE ENVIRONMENT NEEDS

Tailor the display to your needs with on/off toggles for the blue screen. When there is no signal available, a blue screen will show that is ideally designed for dark and low-light environments.

VERSATILE CONNECTIVITY WITH BNC AND HDMI INPUTS

This 27-inch surveillance monitor with BNC Connector supports both analogue and digital video inputs. Easily connect to various video surveillance equipment with HDMI, VGA and BNC in/out ports. BNC port allows connecting CCTV cameras directly to the monitor. With this bezel less security monitor, there is no need for a DVR/converter to get straight to instant monitoring.

Techninė specifikacija

Specifications	
Sandėlio grupė	LCD monitors [+229][-121]
Display	
Display diagonal	68.6 cm (27")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Touchscreen	No
HD type	Full HD
Panel type	VA
Response time	5 ms
Screen shape	Flat

Contrast ratio (typical)	20000000:1
Maximum refresh rate	75 Hz
Display number of colours	16.78 million colours
Display brightness (typical)	300 cd/m²
Anti-glare screen	Yes
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.311 x 0.311 mm
Horizontal scan range	30 - 85 kHz
Digital vertical frequency	48 - 75 Hz
Display diagonal (metric)	69 cm
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	2 W
Design	
Market positioning	Industrial
Product colour	Black
Ports & interfaces	
HDMI	Yes
Headphone out	Yes
VGA (D-Sub) ports quantity	1
HDMI ports quantity	1
HDMI version	1.4
AC (power) in	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot type	Kensington
Tilt adjustment	Yes
Tilt angle range	-5 - 20°
Power	

Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	19.8 kWh
Power consumption (typical)	20 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.2 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 85%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	613.8 mm
Depth (with stand)	226.5 mm
Height (with stand)	453.8 mm
Weight (with stand)	4.5 kg
Width (without stand)	613.8 mm
Depth (without stand)	47.4 mm
Height (without stand)	366.6 mm
Weight (without stand)	4.1 kg
Packaging data	
Package width	6780 mm
Package depth	134 mm
Package height	545 mm
Package weight	6.1 kg
Packaging content	
Cables included	AC, Audio
Quick start guide	Yes
Other features	
Certification	CE LVD WEEE RoHS REACH UKCA EAC

Matmenys ir svoris

Matmenys (l × P × A)	54,00cm × 68,00cm × 14,00cm
----------------------	-----------------------------

Svoris	6,20kg
--------	--------