



**Optoma X309ST**  
**data projector**  
**Desktop**  
**projector 3700**  
**ANSI lumens**  
**DLP XGA**  
**(1024x768) 3D**  
**White**

Modelis: E9PD7DQ01EZ1

Gamintojas: OPTOMA

EAN: 5055387664975

Prekės kodas: 582202

**421.00€**

Remote control included: Yes | Projection technology: DLP | Composite video in: 1 | PC Audio out: Yes  
| Analog signal format system: SECAM 4.25/4.4 | Projector brightness: 3700 ANSI lumens | Analog  
signal format system: PAL 4.43 | Number of built-in speakers: 1 | Fixed focal length: 7.15 mm |  
Analog signal format system: NTSC J | On Screen Display (OSD) languages: Turkish | On Screen  
Display (OSD) languages: German | On Screen Display (OSD) languages: Italian | On Screen Display  
(OSD) languages: Dutch | Supported 3D formats: Frame packing | Analog signal format system:  
SECAM K1 | Built-in speaker(s): Yes | On Screen Display (OSD) languages: Simplified Chinese | On  
Screen Display (OSD) languages: Danish | Serial interface type: RS-232 | On Screen Display (OSD)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be  
išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

languages: Finnish | On Screen Display (OSD) languages: Farsi | On Screen Display (OSD) languages: Spanish | Lamp power: 203 W | Contrast ratio (typical): 25000:1 | AC (power) in: Yes | Analog signal format system: SECAM L | Number of OSD languages: 25 | On Screen Display (OSD) languages: Greek | On Screen Display (OSD) languages: Swedish | On Screen Display (OSD) languages: Hungarian | On Screen Display (OSD) languages: Arabic | On Screen Display (OSD) languages: Portuguese | Supported 3D formats: Side by side | Service life of light source: 6000 h | On Screen Display (OSD) languages: English | On Screen Display (OSD) languages: Norwegian | Smart TV: No | On Screen Display (OSD) languages: Vietnamese | Supported 3D formats: Top and bottom | On Screen Display (OSD) languages: Russian | On Screen Display (OSD) languages: Czech | RMS rated power: 10 W | HDMI connector type: Full-size | On Screen Display (OSD) languages: Polish | On Screen Display (OSD) languages: Indonesian | PC Audio in: Yes | Supported aspect ratios: 4:3 | Lamps quantity: 1 lamp(s) | On Screen Display (OSD) languages: Traditional Chinese | On Screen Display (OSD) languages: French | On Screen Display (OSD) languages: Romanian | PC in (D-Sub): Yes | Password protection: Yes | Warnings: Avoid placing the projector in high humidity areas to prevent damage to the unit. | Market positioning: Presentation | Keystone correction, vertical: -40 - 40° | Ceiling mounting supported: Y | Light source type: Lamp | Service life of light source (economic mode): 10000 h | Projector native resolution: XGA (1024x768) | Projection distance: 0.4 - 3.1 m | Offset: 115% | Power consumption (standby): 0.5 W | On Screen Display (OSD) languages: Japanese | Warnings: Be careful when replacing the projector lamp as it can be very hot. | Throw ratio: 0.617:1 | Warnings: Do not look directly into the lens of the projector during operation to avoid damage to your eyes. | Uniformity: 75% | Screen size compatibility: 810.3 - 6281.4 mm (31.9 - 247.3") | Supported aspect ratios: 16:9 | HDMI version: 1.4a | Full HD: No | Depth: 244 mm | Ethernet LAN: No | Cable lock slot type: Kensington | Built-in display: No | 3D: Yes | Analog signal format system: SECAM G | Cable lock slot: Yes | Supported video modes: 720p | Supported video modes: 480i | Native aspect ratio: 4:3 | Analog signal format system: PAL D | Analog signal format system: SECAM B | Analog signal format system: SECAM D | Horizontal scan range: 15.38 - 91.15 kHz | AC input voltage: 100 - 240 V | Quantity per pack: 1 pc(s) | Analog signal format system: PAL B | Analog signal format system: PAL G | Analog signal format system: PAL H | Analog signal format system: PAL N | Manual: Yes | Supported video modes: 576i | Analog signal format system: PAL | Analog signal format system: SECAM | Supported graphics resolutions: 640 x 480 (VGA) | Card reader integrated: No | VGA (D-Sub) ports quantity: 2 | Vertical scan range: 50 - 85 Hz | Batteries included: Yes | Supported video modes: 1080i | Analog signal format system: NTSC 4.43 | Supported graphics resolutions: 1024 x 768 (XGA) | Power consumption (typical): 187 W | Analog signal format system: PAL I | Analog signal format system: NTSC | Analog signal format system: NTSC 3.58 | Supported graphics resolutions:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shoppro.lt](http://www.shoppro.lt) | [info@shoppro.lt](mailto:info@shoppro.lt) | +370 693 39903

1280 x 800 (WXGA) | USB 2.0 ports quantity: 1 | Analog signal format system: SECAM K | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 1600 x 1200 (UXGA) | Width: 316 mm | HDMI ports quantity: 1 | Supported graphics resolutions: 1280 x 768 (WXGA) | Weight: 3 kg | Supported video modes: 576p | Supported video modes: 480p | Supported video modes: 1080p | Supported graphics resolutions: 1280 x 1024 (SXGA) | Analog signal format system: NTSC M | Analog signal format system: PAL M | AC input frequency: 50/60 Hz | Power source: AC | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | DVI port: No | Product type: Desktop projector | Wi-Fi: No | Noise level: 26 dB | Power consumption (max): 225 W | Cables included: AC | Height: 108 mm | Product colour: White | On Screen Display (OSD): Yes