



IP CAMERA DAHUA IPC- HFW2849S-S-IL- 0280B

Modelis: IPC-HFW2849S-S-IL-0280B

Gamintojas: DAHUA

EAN: 6923172581570

Prekės kodas: 582812

139.98€

Certification: LVD: EN62368-1 EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B 2023-02-22 | Lens type: Fixed focal length lens | Number of lenses: 1 | Lens viewing angle, diagonal: 132° | Lens viewing angle, vertical: 58° | Lens viewing angle, horizontal: 111° | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Warnings: The product contains electronic components do not dispose of with the normal household waste. | Number of illumination LEDs: 2 | White balance: Auto | Bit rate: H.264: 32 kbps-8192 kbps H.265: 12 kbps-8192 kbps | White balance: Street lamp | Minimum illumination: 0.008 lx | Back Light Compensation (BLC): Yes | Number of cameras: 1 | Ethernet LAN: Yes | Night vision distance: 30 m | White balance: Natural | White balance: Outdoor | LED type: IR / White light LED | Housing material: Metal | White balance: Manual | Wide Dynamic Range (WDR): 120 dB | Depth: 166.2 mm | Ethernet interface type: Fast Ethernet | Highlight Compensation (HLC): Yes | Height: 70 mm | Power consumption (max): 5 W | Video compression formats: H.264+ | Audio formats supported: G.711a | Sensor type: CMOS | Audio formats supported: G.711Mu | Built-in HDD: No | Video motion detection: Yes | Weight: 470 g | Wi-Fi:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

No | Focal length range: 2.8 mm | Number of users: 20 user(s) | Closest focusing distance: 1.5 m | Video compression formats: H.264H | Audio formats supported: G.726 | International Protection (IP) code: IP67 | Supported graphics resolutions: 1280 x 720 | Supported graphics resolutions: 2880 x 1620 | Audio formats supported: PCM | Progressive scan: Yes | Video compression formats: H.264B | Maximum resolution: 3840 x 2160 pixels | Type: IP security camera | Pan range: 0 - 360° | Supported graphics resolutions: 352 x 288 | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 2304 x 1296 | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 1280 x 960 | Video compression formats: H.265 | Video compression formats: H.265+ | Mobile operating systems supported: Android | Maximum aperture number: 1.6 | Video compression formats: H.264 | Bluetooth: No | Web-based management: Yes | Connectivity technology: Wired | ROM capacity: 128 MB | Tilt angle range: 0 - 90° | Operating temperature (T-T): -40 - 55 °C | Supported graphics resolutions: 1920 x 1080 | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 2688 x 1520 | Video streaming: Yes | Supported graphics resolutions: 3072 x 2048 | Mobile operating systems supported: iOS | Internal memory: 256 MB | Product colour: White | Camera shutter speed: 1/3 - 1/100000 s | Power consumption (Power over Ethernet (PoE)): 5.9 W | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Number of sensors: 1 | Region of Interest (ROI) encoding: Yes | Video compression formats: M-JPEG | Networking standards: IEEE 802.3af | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Mounting type: Ceiling/wall | Storage temperature (T-T): -40 - 55 °C | Total megapixels: 8 MP | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Night vision: Yes | Built-in microphone: Yes | Power source type: DC, PoE | Quality of Service (QoS) support: Yes | Power consumption (typical): 2.7 W | Noise reduction: Yes | Web browser: Yes | Supported graphics resolutions: 2048 x 1536 (QXGA) | Supported graphics resolutions: 3072 x 1728 | Width: 70 mm | Placement supported: External / Internal | Frame rate: 30 fps | DC output voltage: 12 | Supported graphics resolutions: 3840 x 2160 | Operating relative humidity (H-H): 0 - 95% | Adjustment shutter speed: Auto/Manual | Form factor: Tube/dome