



ZyXel GS2220-50-EU0101F network switch Managed L2 Gigabit Ethernet (10/100/1000) Black

Modelis: GS2220-50-EU0101F

Gamintojas: ZYXEL

EAN: 4718937607525

Prekės kodas: 583223

532.99€

Certification: LVD, BSMI FCC 15 A, CE EMC A, BSMI ENC RoHS A | Port mirroring: Yes | Networking standards: IEEE 802.1x | Storage relative humidity (H-H): 10 - 95% | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Security algorithms: SNMPv2 | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Packet buffer memory: 1.5 MB | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Security algorithms: SNMP | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | MAC address table: 16000 entries | Networking standards: IEEE 802.1ab | Security algorithms: SSL/TLS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Switch type: Managed | Operating temperature

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(T-T): 0 - 50 °C | Link aggregation: Yes | Harmonized System (HS) code: 85176990 | Package weight: 3.97 kg | Internal memory: 256 MB | AC input voltage: 100 - 240 V | Heat dissipation: 125.829 BTU/h | Mean time between failures (MTBF): 660245 h | 10G support: No | DHCP features: DHCP client | DHCP features: DHCP relay | System event log: Yes | Networking standards: IEEE 802.1w | Security algorithms: SSH-2 | Fiber ethernet cabling technology: 1000BASE-X | Access Control List (ACL): Yes | Cables included: AC | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Authentication type: IEEE 802.1x, RADIUS | Authentication: Guest VLAN, MAC-based authentication | DHCP features: DHCPv6 relay | Product colour: Black | Operating relative humidity (H-H): 10 - 95% | DHCP features: DHCP snooping | Switch layer: L2 | Height: 44.5 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | AC input frequency: 50 - 60 Hz | Virtual LAN features: Protocol-based VLAN | Weight: 2.9 kg | Switching capacity: 100 Gbit/s | Power over Ethernet (PoE): No | Width: 440 mm | Multicast support: Yes | Fiber ports quantity: 2 | Rack mounting: Yes | Power consumption (max): 36.9 W | Forwarding rate: 74 Mpps | VLAN support: Yes | Flash memory: 32 MB | Copper ethernet cabling technology: 1000BASE-T | Noise level: 47.3 dB | Basic switching RJ-45 Ethernet ports quantity: 44 | Spanning tree protocol: Yes | Copper ethernet cabling technology: 10BASE-TX | Broadcast storm control: Yes | Fiber optic connector: SFP | Configuring Location Settings (CLI): Yes | Flow control support: Yes | Virtual LAN features: Port-based VLAN | Virtual LAN features: Voice VLAN | Package height: 90 mm | Package depth: 289 mm | Depth: 200 mm | Virtual LAN features: Private VLAN | Rate limiting: Yes | Package width: 496 mm | DHCP features: DHCPv6 client | Combo SFP ports quantity: 4 | IGMP snooping: Yes