

LG 49UH7Q-E Signage Display Digital signage flat panel 124.5 cm (49") LED 700 cd/m² 4K Ultra HD Black WebOS 24/7

Gamintojas: **LG** · Modelis: **49UH7Q-E.AEU** · EAN: **8806096654576** · Prekės kodas: **583378**



1 007,91 €

Kaina su PVM

Be PVM: **832,98 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ HDR Support
- ✓ Slim&Even Bezel
- ✓ webOS Smart Platform



Aprašymas

Superb Picture Quality with Ultra HD Resolution

With the resolution of UHD, it makes the colors and details of the content vivid and realistic.

Even & Slim Bezel Design

The UH7Q-E series features perfectly balanced horizontal and vertical slim bezels, creating a visually harmonious display solution. Its specialized design simplifies installation in retail environments while delivering a truly immersive viewing experience..

Convenient webOS Platform

The UH7Q-E is equipped with a high-performance SoC that allows for multiple tasks to be performed without a separate media player. The webOS platform provides app development tools with an intuitive UI that enhances user convenience, and includes webOS partner apps to create an SI-friendly environment.

Comprehensive Security

webOS Signage goes beyond security measures at the operating system (OS) level. LG Shield employs a five-tiered defense system, encompassing server, application, operating system, system, and hardware. Each layer operates independently, providing comprehensive protection against various threats. Also webOS platform support ETSI EN 303 645.

SuperSign Solutions

SuperSign is an integrated and intuitive content management solution for creative and organized digital signage content in your space, connecting customers to a range of services with convenient user experiences. There are a variety of versions such as SuperSign Cloud, so discover and enjoy the version that best fits you.

Techninė specifikacija

Specifications	
Sandėlio grupė	Digital Signage [+35][-167]
Display	
Display diagonal	124.5 cm (49")
Display technology	LED
Display resolution	3840 x 2160 pixels
Display brightness	700 cd/m²
HD type	4K Ultra HD
Touchscreen	No
Panel type	IPS
LED backlight	Yes
LED backlighting type	Edge-LED
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1100:1
Contrast ratio (dynamic)	1000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Rated lifetime	50000 h
Colour depth	10 bit
High Dynamic Range (HDR) supported	Yes
Native refresh rate	60 Hz
Haze rate	25%

Colour gamut	95%
Ports & interfaces	
HDMI ports quantity	2
DVI port	No
DisplayPorts quantity	1
USB port	Yes
USB ports quantity	2
USB version	2
USB connector type	USB Type-A, USB Type-C
USB Power Delivery (USB PD)	Yes
Ethernet LAN (RJ-45) ports	1
Audio (L/R) out	1
RS-232C	Yes
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Digital signage flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Panel mounting interface	300 x 300 mm
Bezel colour	Black
Performance	
Purpose	Universal
On Screen Display (OSD) languages	Multi
Operating hours (hours/days)	24/7
International Protection (IP) code	IP5X
Power	
Power consumption (typical)	87 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.5 W
Power consumption (max)	134 W

Energy efficiency class (SDR)	G
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	86.7 kWh
AC input voltage	100-240 V
AC input frequency	50/60 Hz
Computer system	
Computer system	Yes
Built-in processor	No
Computer system type	System on Chip (SoC)
Internal memory	16 GB
Operating system installed	WebOS
Operating system version	8
Weight & dimensions	
Display width	1104.3 mm
Display depth	29.7 mm
Display height	645.5 mm
Display weight	13.6 kg
Packaging data	
Package width	1215 mm
Package depth	142 mm
Package height	742 mm
Package weight	16.1 kg
Packaging content	
Tilt angle	15°
Remote control included	Yes
Cables included	AC, USB Type-C
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%
Brand-specific features	
LG technologies (AV/TV)	Smart Energy Saving, Local Network Sync, Control Manager, Local Contents Scheduling, Booting Logo Image, Video Tag, Gapless Playback, ISM Method, Group Manager, No Signal Image, RS232C Sync, Status Mailing, Setting Data Cloning, Fail over, SI Server Setting
Sensors	

Temperature sensor	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	No
Security algorithms	SNMP
Features	
Wall mountable	Yes
Technical details	
Sustainability certificates	ErP, ENERGY STAR
Compliance certificates	Federal Communications Commission (FCC), KC, CE
Other features	
Safety	CB / NRTL
Power supply type	Internal
Bezel width	1.14 cm
Plug and Play	Yes