



TP-Link Archer AC1200 Wireless Dual Band 4G LTE Router

Modelis: Archer MR400

Gamintojas: TP-LINK

EAN: 6935364080662

Prekės kodas: 583813

97.99€

VPN support: PPTP, L2TP, IPSec | Receiver sensitivity: 5GHz: 11a 54M: -74dBm 11ac HT20: -67dBm 11ac HT40: -64dBm 11ac HT80 : -60dBm 11n HT20: -71dBm 11n HT40: -70dBm 2.4G: 11g 54M: -76dBm 11n HT20: -73dBm 11n HT40: -67dBm | Certification: CE, RoHS | USB port: No | Dynamic DNS (DDNS): Yes | Guest access: Yes | DHCP server: Yes | Operating relative humidity (H-H): 10 - 90% | 3G standards: HSPA | Ethernet LAN interface type: Fast Ethernet | Firewall security: DoS, SPI | Transmit power: CE: 20dBm(2.4GHz), 23dBm(5GHz) | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | On/off switch: Yes | SIM card type: MicroSIM | WAN connection type: RJ-45 | Harmonized System (HS) code: 85176990 | Ethernet WAN: Yes | Width: 174 mm | Universal Plug and Play (UPnP): Yes | DoS attack prevention: Yes | Ethernet LAN: Yes | VPN tunnels quantity: 10 | 2G standards: Edge | SIM card slot: Yes | 3G standards: DC-HSPA+ | DSL WAN: No | GSM bands supported: 850 | GSM bands supported: 1900 MHz | 3G bands supported: 900 | Package height: 70 mm | Port forwarding: Yes | 3G bands supported: 2100 MHz | DMZ support: Yes | Mac compatibility: Yes | GSM bands supported: 900 | Wi-Fi standards: 802.11g | Detachable antenna(s): Yes | 4G bands supported: 2600 MHz | Wi-Fi standards: Wi-Fi 4 (802.11n) | WLAN data transfer rate (second band):

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

867 Mbit/s | Wi-Fi standards: 802.11a | Wall mountable: Yes | Mac operating systems supported: MacOS | 2G standards: GSM | Cabling technology: 10/100Base-T(X) | 2G standards: GPRS | Wi-Fi standards: 802.11b | Wi-Fi standards: Wi-Fi 5 (802.11ac) | GSM bands supported: 1800 | Quick installation guide: Yes | VPN server: PPTP VPN, IPSec VPN , OpenVPN | Depth: 124.5 mm | Package width: 307 mm | 3G standards: UMTS | Package depth: 223 mm | WLAN data transfer rate (max): 867 Mbit/s | WPS push button: Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | 4G: Yes | Output voltage: 12 V | 3G: Yes | Antennas quantity: 2 | AC adapter included: Yes | 4G bands supported: 1800 | 4G bands supported: 2100 | 4G bands supported: 800 | Storage relative humidity (H-H): 5 - 90% | 4G standard: LTE | Access Control List (ACL): Yes | Operating temperature (T-T): 0 - 40 °C | WLAN data transfer rate (first band): 450 Mbit/s | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | 4G bands supported: 900 | Supported network protocols: IPv4, IPv6 | Output current: 1.5 A | Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to water or moisture. | Firewall: Yes | Memory card slot(s): No | Linux operating systems supported: Yes | Windows operating systems supported: Windows XP Home | Windows operating systems supported: Windows NT | Windows operating systems supported: Windows 2000 | Windows operating systems supported: Windows 98SE | Windows operating systems supported: Windows 7 | VPN Passthrough: Yes | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Windows operating systems supported: Windows XP Professional x64 | Windows operating systems supported: Windows 8 | Product type: Tabletop router | Windows operating systems supported: Windows XP Home x64 | Cables included: LAN (RJ-45) | Antenna design: Internal & external | Height: 33.5 mm | Windows operating systems supported: Windows XP Professional | Mobile network generation: 4G | Windows operating systems supported: Windows 10 | 3G/4G USB modem compatibility: No | Security algorithms: WPA | Web-based management: Yes | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Power source type: DC | Security algorithms: 128-bit WEP | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11a | DC-in jack: Yes | Package type: Box | Security algorithms: WPA2-PSK | LED indicators: LAN, Power, Status, WLAN | Ethernet LAN (RJ-45) ports: 3 | DHCP client: Yes | Networking standards: IEEE 802.11b | Security algorithms: WPA-PSK | Product colour: Black | Stateful Packet Inspection (SPI): Yes | Package weight: 670 g | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 10 | Reset button: Yes