



PowerWalker VI 850 SHL Schuko uninterruptible power supply (UPS) Line- Interactive 0.85 kVA 480 W 2 AC outlet(s)

Modelis: VI 850 SHL

Gamintojas: POWER WALKER

EAN: 4260074976489

Prekės kodas: 584035

111.99€

Bundled software: WinPower | Warnings: Keep away from sources of fire and water. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Weight: 5 kg | Product colour: Black | AC outlets quantity: 2 AC outlet(s) | LED indicators: Yes | Battery voltage: 12 V | Input frequency: 50/60 Hz | Battery capacity: 9 Ah | Power protection features: Overload | Output power factor: 0.56 | Package height: 226 mm | Number of batteries supported: 1 | Typical backup time at full load: 0.1 min | Automatic Voltage Regulation (AVR): Yes | Efficiency: 95% | AC outlet types: Type F | UPS topology: Line-Interactive | Depth: 290 mm | Package width: 139 mm | Surge protection features:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Modem | Output voltage regulation: 10% | Cooling type: Passive | Operating relative humidity (H-H): 0 - 90% | Surge protection features: Fax | Manual: Yes | Output power capacity: 0.85 kVA | Form factor: Tower | Operating temperature (T-T): 0 - 40 °C | Charging current: 1.2 A | Resource CD: Yes | Output frequency regulation: 1 Hz | Harmonized System (HS) code: 85078000 | Output power: 480 W | Modem (RJ-11) ports: 2 | Number of type F outputs: 2 | Display type: LCD | Surge protection: Yes | Typical backup time at half load: 6 min | Surge protection features: Telephone | Nominal output voltage: 230 V | Width: 100 mm | Battery recharge time: 4 h | USB 2.0 ports quantity: 1 | Input operation voltage (max): 280 V | Input operation voltage (min): 170 V | Height: 143 mm | Cables included: USB cable