



PowerWalker VFI 1000 ICR IoT Double- conversion (Online) 1 kVA 1000 W 8 AC outlet(s)

Modelis: VFI 1000 ICR IOT PF1

Gamintojas: POWER WALKER

EAN: 4260074982879

Prekės kodas: 584053

488.99€

Warnings: Keep away from sources of fire and water. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Package width: 498 mm | Charging current: 1.5 A | Serial interface: Yes | Number of batteries supported: 3 | Cooling type: Active | Waveform: Pure sine | Form factor: Rackmount/Tower | Noise level: 45 dB | Output operation voltage (min): 200 V | Output voltage Total Harmonic Distortion (THD): 1% | Rack capacity: 2U | Package height: 240 mm | Weight: 14.3 kg | Power plug: C14 coupler | AC outlets quantity: 8 AC outlet(s) | Input power factor: 0.99 | Crest factor: 3:1 | ECO mode: Yes | Efficiency (On-line mode): 89% | Battery capacity: 7 Ah | Output power factor: 1 | Serial ports quantity: 1 | Input frequency: 40/70 Hz | Battery recharge time: 3 h | Emergency

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Power Off (EPO) connector: Yes | Input operation voltage (min): 160 V | UPS topology: Double-conversion (Online) | Output operation voltage (max): 240 V | Battery voltage: 12 V | Operating temperature (T-T): 0 - 45 °C | LED indicators: Yes | Input operation voltage (max): 300 V | Depth: 445 mm | Power protection features: Overload | Width: 438 mm | USB port: Yes | Output power: 1000 W | Serial interface type: RS-232 | Operating relative humidity (H-H): 0 - 95% | Display type: LCD | Output power capacity: 1 kVA | Output voltage regulation: 1% | AC outlet types: C13 coupler | Built-in fan: Yes | Product colour: Black | Manual: Yes | Height: 85.5 mm | Input current Total Harmonic Distortion (THD): 5% | Emergency Power Off (EPO): Yes | Rack mount kit: Yes | Cables included: Input power cable, Output power cable, USB cable