



PowerWalker VFI 1500 ICR IoT Double- conversion (Online) 1.5 kVA 1500 W 8 AC outlet(s)

Modelis: VFI 1500 ICR IOT PF1

Gamintojas: POWER WALKER

EAN: 4260074982886

Prekės kodas: 584054

562.99€

Crest factor: 3:1 | Output power factor: 1 | Height: 85.5 mm | Input current Total Harmonic Distortion (THD): 5% | Battery capacity: 9 Ah | Package width: 498 mm | Charging current: 1.5 A | Number of batteries supported: 3 | Form factor: Rackmount/Tower | Noise level: 45 dB | Serial interface: Yes | Emergency Power Off (EPO) connector: Yes | AC outlets quantity: 8 AC outlet(s) | Package height: 240 mm | Output voltage Total Harmonic Distortion (THD): 1% | Weight: 15.8 kg | Waveform: Sine | ECO mode: Yes | Output operation voltage (min): 200 V | USB 2.0 ports quantity: 1 | Serial ports quantity: 1 | Input frequency: 40/70 Hz | Battery recharge time: 3 h | UPS topology: Double-conversion (Online) | Output operation voltage (max): 240 V | Battery voltage: 12 V | Serial interface type: RS-232 | Depth: 445 mm | Manual: Yes | Width: 438 mm | USB port: Yes | Operating relative

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

humidity (H-H): 0 - 95% | Display type: LCD | Output power: 1500 W | Output voltage regulation: 1% |
Output power capacity: 1.5 kVA | AC outlet types: C13 coupler | Operating temperature (T-T): 0 - 45
°C | Efficiency: 89% | Emergency Power Off (EPO): Yes | Power plug: C14 coupler | Input operation
voltage (min): 110 V | Cables included: Input power cable, Output power cable, USB cable | Hot-swap
battery: Yes | LED indicators: Yes | Input operation voltage (max): 300 V