



TP-LINK 4G+ Cat6 AC1200 Wireless Dual Band Gigabit Router

Modelis: Archer MR600

Gamintojas: TP-LINK

EAN: 6935364089832

Prekės kodas: 584059

134.00€

Receiver sensitivity: 5 GHz: 11a 54M: -74 dBm 11ac HT20: -66 dBm 11ac HT40: -63 dBm 11ac HT80 : -59 dBm 11n HT20: -73 dBm 11n HT40: -70 dBm 2.4 GHz: 11g 54M: -74 dBm 11n HT20: -72 dBm 11n HT40: -69 dBm | VPN support: PPTP VPN, IPSec VPN , OpenVPN | Certification: CE, RoHS | Ethernet LAN data rates: 1000 Mbit/s | Mac operating systems supported: Yes | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Ethernet LAN data rates: 10 | Networking standards: IEEE 802.11a | Wi-Fi standards: 802.11g | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | DC-in jack: Yes | DHCP client: Yes | AC input voltage: 100 - 240 V | Wi-Fi standards: 802.11b | Operating temperature (T-T): 0 - 40 °C | Package type: Box | 3G: Yes | Antennas quantity: 2 | Reset button: Yes | Package depth: 223 mm | Networking standards: IEEE 802.11ac | 4G: Yes | Output voltage: 12 V | Package width: 307 mm | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | AC adapter included: Yes | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN interface type: Gigabit Ethernet | LED indicators: LAN, Power, WLAN | Ethernet LAN

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

data rates: 100 | Filtering: Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Stateful Packet Inspection (SPI): Yes | Security algorithms: WPA2-PSK | WLAN data transfer rate (max): 867 Mbit/s | Networking standards: IEEE 802.11b | AC input frequency: 50 - 60 Hz | Ethernet WAN: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Windows operating systems supported: Yes | Security algorithms: 128-bit WEP | Security algorithms: WPA | Width: 229 mm | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi standards: 802.11a | Package height: 70 mm | Ethernet LAN (RJ-45) ports: 4 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Cables included: LAN (RJ-45) | Product colour: Black | Quick installation guide: Yes | Power source type: AC, DC | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not expose the device to water or moisture. | Number of guest networks (2.4 GHz): 1 | Routing protocols: IP | 4G standard: LTE | WAN connection type: RJ-45 | Antenna design: External | Mobile network generation: 4G | Harmonized System (HS) code: 85176990 | 4G bands supported: 700 | 4G bands supported: 2300 | Product type: Tabletop router | WLAN data transfer rate (first band): 867 Mbit/s | Number of products included: 1 pc(s) | DSL WAN: No | 4G bands supported: 2600 MHz | 4G bands supported: 850 | 4G bands supported: 2500 MHz | 4G bands supported: 900 | Height: 37 mm | Port triggering: Yes | Detachable antenna(s): Yes | 4G bands supported: 1800 | Number of guest networks (5 GHz): 1 | WPS push button: Yes | Firewall: Yes | 3G standards: HSPA | Guest access: Yes | Wall mountable: No | SIM card type: MicroSIM | Dual SIM support: No | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | 3G standards: UMTS | 3G bands supported: 850 | URL filtering: Yes | 3G bands supported: 900 | 3G bands supported: 2100 MHz | USB port: No | Universal Plug and Play (UPnP): Yes | DoS attack prevention: Yes | 4G bands supported: 2100 | 4G bands supported: 800 | 3G/4G USB modem compatibility: No | Ethernet LAN: Yes | Depth: 160 mm | Firewall security: Domain Filter, IP, MAC Address Binding | Dynamic DNS (DDNS): Yes | DHCP server: Yes | SIM card slot: Yes | DMZ support: Yes | Port forwarding: Yes | Supported network protocols: IPv4, IPv6 | Memory card slot(s): No | Output current: 1.5 A | 5G: No | WLAN data transfer rate (second band): 300 Mbit/s | Linux operating systems supported: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Parental control: Yes