



TP-Link Omada AX3000 Ceiling Mount WiFi 6 Access Point



Modelis: EAP653

Gamintojas: TP-LINK

EAN: 4897098685235

Prekės kodas: 584062

110.99€

Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.11a | Security algorithms: HTTPS | Reset button: Yes | Security algorithms: WPA | Depth: 160 mm | Quick start guide: Yes | Syslog: Yes | Cabling technology: 10/100/1000Base-T(X) | Ethernet LAN data rates: 1000 Mbit/s | Ethernet LAN data rates: 10 | Security algorithms: WPA2 | Security algorithms: SNMPv2 | Networking standards: IEEE 802.11g | Security algorithms: SNMP | Security algorithms: SSH | Networking standards: IEEE 802.11ac | Security algorithms: SNMPv3 | Number of users: 250 user(s) | Width: 160 mm | Networking standards: IEEE 802.11h | Mounting kit: Yes | VLAN support: Yes | Rate limiting: Yes | Networking standards: IEEE 802.11b | Ethernet LAN data rates: 100 | Operating temperature (T-T): 0 - 40 °C | Airtime Fairness (ATF): Yes | Package type: Box | DC-in jack: Yes | Automatic channel scanning: Yes | Ethernet LAN (RJ-45) ports: 1 | Maximum data transfer rate (2.4 GHz): 574 Mbit/s | Band steering: Yes | Power over Ethernet (PoE): Yes | Height: 33.6 mm | Fit AP mode features: Mesh networking | Automatic channel selection: Yes | DC voltage range: 12 V | Operating relative humidity (H-H): 10 - 90% | Maximum data transfer rate (5 GHz): 2402 Mbit/s |

Spread spectrum method: OFDMA | MIMO type: Multi User MIMO | Flow control support: Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Placement: Ceiling, Wall | Quantity per pack: 1 pc(s) | LED indicators: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | 6 GHz: No | Transmitting power (CE): 27 dBm | Transmitting power (FCC): 22 dBm | BeamForming: Yes | 2.4 GHz: Yes | Web-based management: Yes | MAC address filtering: Yes | Maximum data transfer rate: 2976 Mbit/s | 5 GHz: Yes | Antenna type: Internal | Firmware upgradeable: Yes | Frequency band: 2.4 - 5 GHz | Product colour: White | MIMO: Yes | Warnings: Electronic products should be recycled at specialist electronic waste collection facilities. | Warnings: Do not expose to prolonged moisture. | Warnings: Avoid direct contact with water.